

UNIUNION TRANSISTORS INDEX

2N489-2N4949

TYPE	REPLACEMENT	PAGE NUMBER	P _D (mW)	R _{BB} (kΩ)	η	I _V (min) (mA)	I _P (max) (μA)	I _{EO} @V _{EB2} (μA @ V max)	V _{E(SAT)} I _E @50 mA
2N489			450	6.8	0.62	8.0	20	12 @ 60	5.0
2N489A			450	6.8	0.62	8.0	15	12 @ 60	4.0
2N489B			450	6.8	0.62	8.0	6.0	0.2 @ 60	4.0
2N490			450	9.1	0.62	8.0	20	12 @ 60	5.0
2N490A			450	9.1	0.62	8.0	15	12 @ 60	4.0
2N490B			450	9.1	0.62	8.0	6.0	0.2 @ 60	4.0
2N490C			450	9.1	0.51				
2N491			450	6.8	0.68	8.0	20	12 @ 60	5.0
2N491A			450	6.8	0.68	8.0	15	12 @ 60	4.3
2N491B			450	6.8	0.68	8.0	6.0	0.2 @ 60	4.3
2N492			450	9.1	0.68	8.0	20	12 @ 60	5.0
2N492A			450	9.1	0.68	8.0	15	12 @ 60	4.3
2N492B			450	9.1	0.68	8.0	6.0	0.2 @ 60	4.3
2N492C			450	9.1	0.56				
2N493			450	6.8	0.75	8.0	20	12 @ 60	5.0
2N493A			450	6.8	0.75	8.0	15		
2N493B			450	6.8	0.75	8.0	6.0	0.2 @ 60	5.0
2N494			450	9.1	0.75	8.0	20	12 @ 60	5.0
2N494A			450	9.1	0.75	8.0	15	12 @ 60	4.6
2N494B			450	9.1	0.75	8.0	6.0	0.2 @ 60	4.6
2N494C			450	9.1	0.62	8.0	2.0	0.02 @ 60	4.6
2N1671			450	9.1	0.62	8.0	25	12 @ 30	5.0
2N1671A			450	9.1	0.62	8.0	25	12 @ 30	5.0
2N1671B			450	9.1	0.62	8.0	6.0	0.2 @ 30	5.0
2N1671C			450	4.1 -9.1					
2N2160			450	4.0 -12	0.47 -0.80	8.0	25	12 @ 30	
2N2417			390	0.68	0.62	8.0	20	12 @ 60	5.0
2N2417A			390	0.68	0.62	8.0	20	12 @ 60	4.0
2N2417B			300	6.8	0.51 -0.62	8.0	6.0	0.2 @ 30	4.0
2N2418			390	0.68	0.62	8.0	20	12 @ 60	5.0
2N2418A			390	9.1	0.62	8.0	20	12 @ 60	4.0
2N2418B			300	9.1	0.51 - 0.62	8.0	6.0	0.2 @ 60	4.0
2N2419			390	4.7 -6.8	0.68	8.0	20	12 @ 60	5.0
2N2419A			390	6.8	0.68	8.0	20	12 @ 60	4.3
2N2419B			300	6.8	0.56 -0.68	8.0	6.0	0.2 @ 30	4.3
2N2420			390	9.1	0.68	8.0	20	12 @ 60	5.0
2N2420A			390	9.1	0.68	8.0	20	12 @ 60	4.3
2N2420B			300	9.1	0.56 -0.68	8.0	6.0	0.2 @ 30	4.3
2N2421			390	6.8	0.75	8.0	20	12 @ 60	5.0
2N2421A			390	6.8	0.75	8.0	20	12 @ 60	4.6
2N2421B			300	6.8	4.7 -6.8	8.0	6.0	0.2 @ 30	4.6
2N2422			390	9.1	0.75	8.0	20	12 @ 60	5.0
2N2422A			390	9.1	0.75	8.0	20	12 @ 60	4.6
2N2422B			300	9.1	0.62 -0.75	8.0	6.0	0.2 @ 30	
2N2646		4-70	300	4.7 (min)	0.56	4.0	25	12 @ 30	2.0
2N2647		4-70	300	4.7 (min)	0.68	8.0	2.0	0.2 @ 30	2.0
2N2840			300	4.7 -9.1	1.3 -1.5	0.70	10	1.0 @ 30	
2N3406			450			8.0			
2N3479			400	4.7 -9.1	0.47 -0.62	6.0	20	12 @ 30	5.0
2N3480			400	9.1	0.75	4.0	15	12 @ 30	5.0
2N3481			400	9.1	0.85	6.0	15	12 @ 30	5.0
2N3482			400	4.7 -6.8	0.51 -0.62	8.0	2.0	0.02 @ 30	5.0
2N3483			400	9.1	0.72	8.0	2.0	1.0 @ 30	5.0
2N3484			400	9.1	0.85	8.0	2.0	0.2 @ 30	5.0
2N3679			250	9.1	0.80	4.2			
2N3980		4-72	360	8.0					
2N4851		4-74	300	4.7 (min)	0.56 (min)	2.0	2.0	0.1 @ 30	2.5
2N4852		4-74	300	4.7 (min)	0.70 (min)	4.0	2.0	0.1 @ 30	2.5
2N4853		4-74	300	4.7 (min)	0.70 (min)	6.0	0.4	0.05 @ 30	2.5
2N4870		4-78	300	4.0 (min)	0.56 (min)	2.0	5.0	0.05 @ 30	2.5
2N4871		4-78	300	4.0 (min)	0.70 (min)	4.0	5.0	0.05 @ 30	2.5
2N4891			300	4.0 (min)	0.55 (min)	2.0	5.0	0.01 @ 30	4.0
2N4892			300	4.0 (min)	0.51 (min)	4.0	2.0	0.01 @ 30	4.0
2N4893			300	4.0 (min)	0.55 (min)	2.0	2.0	0.01 @ 30	4.0
2N4894			300	4.0 (min)	0.74 (min)	2.0	1.0	0.01 @ 30	4.0
2N4948		4-82	360	4.0 (min)	0.55 (min)	2.0	2.0	0.01 @ 30	2.5
2N4949		4-82	360	4.0 (min)	0.74 (min)	2.0	1.0	0.01 @ 30	2.5