

N-Channel 60-V (D-S) MOSFET

PRODUCT SUMMARY			
V_{DS} (V)	$r_{DS(on)}$ (Ω)	$V_{GS(th)}$ (V)	I_D (A)
60	2 at $V_{GS} = 10$ V	1.0 to 2.5	0.47
	4 at $V_{GS} = 4.5$ V		0.33


FEATURES

- TrenchFET[®] Power MOSFET
- ESD Protected: 2000 V


 Available
RoHS*
 COMPLIANT

APPLICATIONS

- Direct Logic-Level Interface: TTL/CMOS
- Solid-State Relays
- Drivers: Relays, Solenoids, Lamps, Hammers, Display, Memories, Transistors, etc.
- Battery Operated Systems



Ordering Information: 2N7000KL-TR1
 2N7000KL-TR1-E3 (Lead (Pb)-free)

Ordering Information: BS170KL-TR1
 BS170KL-TR1-E3 (Lead (Pb)-free)

ABSOLUTE MAXIMUM RATINGS $T_A = 25$ °C, unless otherwise noted				
Parameter	Symbol	Limit	Unit	
Drain-Source Voltage	V_{DS}	60	V	
Gate-Source Voltage	V_{GS}	± 20		
Continuous Drain Current ($T_J = 150$ °C) ^b	I_D	$T_A = 25$ °C	A	
		$T_A = 70$ °C		
Pulsed Drain Current ^a	I_{DM}	1.0		
Power Dissipation	P_D	$T_A = 25$ °C	W	
		$T_A = 70$ °C		
Maximum Junction-to-Ambient	R_{thJA}	158	°C/W	
Operating Junction and Storage Temperature Range	T_J, T_{stg}	- 55 to 150	°C	

Notes:

a. Pulse width limited by maximum junction temperature.

* Pb containing terminations are not RoHS compliant, exemptions may apply.



SPECIFICATIONS $T_A = 25\text{ }^\circ\text{C}$, unless otherwise noted						
Parameter	Symbol	Test Conditions	Limits			Unit
			Min	Typ	Max	
Static						
Drain-Source Breakdown Voltage	$V_{(BR)DSS}$	$V_{GS} = 0\text{ V}, I_D = 10\text{ }\mu\text{A}$	60			V
Gate-Threshold Voltage	$V_{GS(th)}$	$V_{DS} = V_{GS}, I_D = 250\text{ }\mu\text{A}$	1	2.0	2.5	
Gate-Body Leakage	I_{GSS}	$V_{DS} = 0\text{ V}, V_{GS} = \pm 10\text{ V}$			± 1	μA
Zero Gate Voltage Drain Current	I_{DSS}	$V_{DS} = 60\text{ V}, V_{GS} = 0\text{ V}$ $V_{DS} = 60\text{ V}, V_{GS} = 0\text{ V}, T_J = 55\text{ }^\circ\text{C}$			1 10	
On-State Drain Current ^b	$I_{D(on)}$	$V_{GS} = 10\text{ V}, V_{DS} = 7.5\text{ V}$ $V_{GS} = 4.5\text{ V}, V_{DS} = 10\text{ V}$	0.8 0.5			A
Drain-Source On-Resistance ^b	$r_{DS(on)}$	$V_{GS} = 10\text{ V}, I_D = 0.5\text{ A}$ $V_{GS} = 4.5\text{ V}, I_D = 0.2\text{ A}$		1.1 1.6	2 4	
Forward Transconductance ^b	g_{fs}	$V_{DS} = 10\text{ V}, I_D = 0.5\text{ A}$		550		ms
Diode Forward Voltage	V_{SD}	$I_S = 0.3\text{ A}, V_{GS} = 0\text{ V}$		0.87	1.3	V
Dynamic^b						
Total Gate Charge	Q_g	$V_{DS} = 10\text{ V}, V_{GS} = 4.5\text{ V}$ $I_D \cong 0.25\text{ A}$		0.4	0.6	nC
Gate-Source Charge	Q_{gs}			0.11		
Gate-Drain Charge	Q_{gd}			0.15		μF
Gate Resistance	R_g		173			
Turn-On Time	$t_{d(on)}$ t_r	$V_{DD} = 30\text{ V}, R_L = 150\text{ }\Omega$ $I_D \cong 0.2\text{ A}, V_{GEN} = 10\text{ V}, R_G = 10\text{ }\Omega$		3.8 4.8	10 15	ns
Turn-Off Time	$t_{d(off)}$			12.8	20	
	t_f			9.6	15	

Notes:

- a. Pulse test: $PW \leq 300\text{ }\mu\text{s}$ duty cycle $\leq 2\%$.
- b. Guaranteed by design, not subject to production testing.


Stresses beyond those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

TYPICAL CHARACTERISTICS $25\text{ }^\circ\text{C}$, unless otherwise noted







TYPICAL CHARACTERISTICS 25 °C, unless otherwise noted




On-Resistance vs. Drain Current




Capacitance




Gate Charge



On-Resistance vs. Junction Temperature




Source-Drain Diode Forward Voltage




On-Resistance vs. Gate-Source Voltage


TYPICAL CHARACTERISTICS 25 °C, unless otherwise noted




Threshold Voltage Variance Over Temperature



Single Pulse Power, Junction-to-Ambient



Safe Operating Area



Normalized Thermal Transient Impedance, Junction-to-Ambient

Vishay Siliconix maintains worldwide manufacturing capability. Products may be manufactured at one of several qualified locations. Reliability data for Silicon Technology and Package Reliability represent a composite of all qualified locations. For related documents such as package/tape drawings, part marking, and reliability data, see <http://www.vishay.com/ppg?72705>.



Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.