




Surface Mount Fast Switching Diode



Features:

- Ultra-Small Surface Mount Package
- Fast Switching Speed
- For General Purpose Switching Applications
- High Conductance
- Also Available in Lead Free Version



SOT-523

Max. Rating @ T_A = 25°C unless otherwise specified

Parameter	Symbol	Limits	Unit
Peak repetitive reverse voltage	V _{RRM}	85	V
Working peak reverse voltage	V _{RMS}	85	V
DC blocking voltage	V _R	85	V
RMS reverse voltage	V _{R(RMS)}	60	V
Forward continuous current (Max.)	I _{FM}	155	mA
Single diode loaded		75	
Both diodes loaded			
Repetitive peak forward current	I _{FRM}	500	mA
Non-repetitive peak forward surge current	I _{FSM}	4	A
@t = 1μs		1	
@t = 1ms		0.5	
@t = 1s			
Power dissipation	P _D	150	mW
Thermal resistance junction to ambient	R _{θJA}	833	°C/W
Junction and storage temperature	T _j , T _{STG}	-65 to +150	°C

Electrical Characteristics @ T_A = 25°C unless otherwise specified

Parameter	Symbol	Conditions	Min.	Max.	Unit
Reverse breakdown voltage	V _{(BR)R}	I _R = 100μA	85	-	V
Leakage current	I _R	V _R = 25V	-	30	nA
		V _R = 75V		2	μA
		V _R = 25V, T _j = 150°C		60	μA
		V _R = 75V, T _j = 150°C		100	μA
Forward voltage	V _F	I _F = 1mA	-	0.715	V
		I _F = 10mA		0.855	
		I _F = 50mA		1	
		I _F = 150mA		1.25	
Typical total capacitance	C _T	V _R = 0V, f = 1MHz	-	1.75	pF
Reverse recovery time	t _{rr}	I _F = I _R = 10mA, I _{rr} = 0.1 × I _R , R _L = 100Ω	-	4	ns

Surface Mount Fast Switching Diode



Typical Characteristics @ $T_A = 25^\circ\text{C}$ unless otherwise specified




Fig. 1 Current Derating Curve




Fig. 2 Forward Characteristics




Fig. 3 Typical Reverse Characteristics





Fig. 4 Typical Capacitance vs. Reverse Voltage


Surface Mount Fast Switching Diode



Plastic surface mounted package



SOT-523		
Dim	Min	Max
A	1.5	1.7
B	0.75	0.85
C	0.6	0.8
D	0.15	0.3
G	0.9	1.1
H	0.02	0.1
J	0.1 Typical	
K	1.45	1.75
All Dimensions in mm		



Unit : mm

Package Information

Device	Package	Shipping
BAV99T-7-F	SOT-523	3,000 / Tape & Reel

Part Number Table

Description	Part Number
Surface Mount Fast Switching Diode	BAV99T-7-F

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp is the registered trademark of the Group. © Premier Farnell plc 2012.