





RECTIFIER DIODES

Fast-recovery-diodes

Type	V _{RRM} (V)	I _{FAV} (A)	I _{FSM} (A)	V _F at	I _F (A)	t _{rr} (us)	Case JEDEC
BA 157	400	1.0	35	<1.3	1.0	<0.3	DO15 
BA 158	600						
BA 159	1000						
BY 396	100	3.0	60	<1.3	3.0	<0.4	DO-201 AD 
BY 397	200						
BY 398	400						
BY 399	800						
RGP 30M	1000	3.0	100	<1.3	3.0	<0.4	
BYX 05-100	100	5.0	80	<1.3	5.0	<0.3	TO-220 AC 
BYX 05-200	200						
BYX 05-400	400						
BYX 05-600	600						
BYX 05-800	800						
BYX 05-1000	1000						
BYT 08-100	100	8.0	100	<1.85	20	<0.3	
BYT 08-200	200						
BYT 08-400	400						
BYT 08-600	600						
BYT 08-800	800						
BYT 08-1000	1000						
BYT 12-100	100	12	150	<1.9	30	<0.3	
BYT 12-200	200						
BYT 12-400	400						
BYT 12-600	600						
BYT 12-800	800						
BYT 12-1000	1000						
BYT 25-200	200	25	400	<1.9	50	<0.4	DO-218 
BYT 25-400	400						
BYT 25-600	600						
BYT 25-800	800						
BYT 25-1000	1000						