












EXAMPLE & ORDERING CODE

42R08- 3 1 2 1 - 150 - D3

MECHANICAL MOUNTING CONFIGURATION	
SIDE FLANGE	 =1
CROSS FLANGE	 =2
SNAP-IN	 =3
COLOR Other colors available on request.	
BLACK	=1
GRAY	=2
SOLDER TERMINAL	
 =2	
ELECTRICAL CIRCUIT CONFIGURATION	
	16A 250V 65°C 2+Ground  =1
	16A 250V 155°C 2+Ground  =2
	16A 250V 65°C 2 Pole  =3
PANEL THICKNESS (SNAP-INS ONLY)	
.06 (1.5mm)	=150
.08 (2.0mm)	=200
Additional panel thickness available on request.	.10 (2.5mm) =250
	Add Suffix D3 to Part Number for 20A, 250V =D3

Power connectors rated 16 Amp., 250 VAC, 65°C to 155°C operating temperature. Available 20A for UL and CSA. Units are available with solder lug terminal configurations. Designed for versatile mounting, 42R08 is available in screw or snap-in panel mount and three mechanical mounting configurations.

SPECIFICATIONS

MATERIAL AND FINISH:

Housing:
 Material: Polycarbonate
 Rating: UL 94V-0
 Contacts:
 Material: Copper
 Plating: Tin

ELECTRICAL SPECIFICATIONS:

Insulation Resistance: 100 Megaohm min. @ 500 VDC
 Dielectric Strength: 2000 VAC for 1 minute

Specifications subject to change without notice. (Notice dimensions are shown in parentheses)
 See pages 293-300 for mating power cords.