

MIL-DTL-38999 Series III



ITT

MIL-DTL-38999 Series III Connector

With a proven history of engineering and manufacturing excellence spanning over 90 years, ITT has delivered a broad range of innovative product solutions that have and continue to enable our customers to meet their most demanding design requirements. ITT's design centers provide time proven high quality products and exceptional service to customers through a global network of field application engineers, sales force and manufacturing facilities.

The D38999 Series III meets the stringent MIL-DTL-38999 specifications and is ideally suited for the harsh environments in military and aerospace. This product line is fully qualified under the MIL-C-39029 standards for contacts, MIL-I-81969 for application tools, and MIL-STD-1560 for insert arrangements.



Innovative Interconnect Benefits

- High contact density
- Wire sealing grommets
- Meets all stringent DLA qualifications requirements
- Available Class F (Nickel), Class G and Class W (DD CAD/Nickel) which accommodates up to 500h salt spray resistance.

Product Features

- Superior EMI shielding provides protection up to 65dB at 10 GHZ 100% scoop proof
- Rear release crimp snap-in contacts
- Interfacial seal inhibits electrolytic erosion of contacts.

Applications


- Military Vehicles
- Defense Electronics
- Commercial & Military Aircraft
- Tactical Communications
- Avionics



MIL-DTL-38999 Series III Selection Guide

Max. Voltage	Max. Current	Operating Temp	Durability
1000 - 2300 VAC	1.5 - 23.0 Amps	-65° C to + 200° C	500 Mating Cycles

MIL-DTL-38999 Series III
Product Line Talking Dog



Connector Type	D38999 - MIL-DTL-38999 Series III
Shell Style	D38999/20 - Wall mount receptacle
	D38999/24 - Jam nut receptacle
	D38999/26 - Straight plug, grounded
Service Class	F - Electroless nickel (-85°F to +392°F (-65°C to +200°C)), Aluminum
	G - Electroless nickel plated. Space Grade, Aluminum
	W - Olive drab cadmium over electroless nickel plate (-85°F to +347°F (-65°C to +175°C)), Aluminum
Shell Size	A, B, C, D, E, F, G, H, J
Contact Arrangements	9-35, 9-98, 11-5, 11-35, 11-98, 13-8, 13-98, 13-35, 15-5, 15-15, 15-18, 15-19, 15-35, 15-97, 17-6, 17-8, 17-26, 17-35, 19-11, 19-32, 19-35, 21-11, 21-16, 21-35, 21-39, 21-41, 21-75, 23-21, 23-35, 23-53, 23-55, 25-4, 25-19, 25-24, 25-29, 25-35, 25-43, 25-61
Contact Style	P - Pin contact
	S - Socket contact
	A - Less Pin contacts*
	B - Less Socket contacts*
Polarizing Position	N (Normal), A, B, C, D, E

* Used only when other than power contacts are to be installed (i.e. shielded thermocouple, etc.)
 Note: To order MS connectors less standard power contacts, purchase order must state "Less Contacts"

Visit us online at www.ittcannon.com or these social media networks: **ITT Corporation**



Americas: James Yoshitake 714.628.2182 james.yoshitake@ittcorp.com	Europe: Rob Pulman 44.1256.311512 rob.pulman@ittcorp.com	Asia: Teddy Chan 852.25895830 teddy.chan@ittcorp.com	Japan: Takashi Goto 81.46.257.2012 takashi.goto@ittcorp.com
---	---	---	--