

ELECTRONIC / GLASS FUSES



GSD / GSD-V

Ceramic Body
Fast Acting
5mm x 20 mm
1-1/2" Axial Leads Optional

1/20A through 10A, 250VAC - UL & CSA Recognized
1/20A through 6-3/10A, 250VAC - KEMA Approved
1A through 6-13/10A, 250VAC - BSI Approved
1/20A through 6-3/10A, 250VAC - SEMKO
1/20A-2/10A & 5/16-6-3/10A, 250VAC - VDE Approved
Sheet I IEC 127-2*



GSF / GSF-V

Ceramic Body
Time Delay
5mm x 20 mm
1-1/2" Axial Leads Optional

2/10A through 10A, 250VAC - UL and CSA Recognized
1A through 6-3/10A, 250VAC - SEMKO, BSI, VDE Approved
1A through 10A, 250VAC - MITI Approved
Sheet V IEC 127*



Standard Fuse Ampere Ratings

Standard Fuse Ampere Ratings

CATALOG NUMBER	AXIAL LEAD CAT. NO	AMPERE RATING	VOLTS	IR
GSD1/20	GSD-V1/20	1/20A	250V	1
GSD1/16	GSD-V1/16	1/16A	250V	1
GSD8/100	GSD-V8/100	8/100A	250V	1
GSD1/10	GSD-V1/10	1/10A	250V	1
GSD1/8	GSD-V1/8	1/8A	250V	1
GSD16/100	GSD-V16/100	16/100A	250V	1
GSD2/10	GSD-V2/10	2/10A	250V	1
GSD1/4	GSD-V1/4	1/4A	250V	1
GSD315/1000	GSD-V315/1000	315/1000A	250V	1
GSD4/10	GSD-V4/10	4/10A	250V	1
GSD1/2	GSD-V1/2	1/2A	250V	1
GSD630/1000	GSD-V630/1000	630/1000A	250V	1
GSD8/10	GSD-V8/10	8/10A	250V	1
GSD1	GSD-V1	1A	250V	1
GSD1-1/4	GSD-V1-1/4	1-1/4A	250V	1
GSD1-6/10	GSD-V1-6/10	1-6/10A	250V	1
GSD2	GSD-V2	2A	250V	1
GSD2-1/2	GSD-V2-1/2	2-1/2A	250V	1
GSD3-15/100	GSD-V3-15/100	3-15/100A	250V	1
GSD4	GSD-V4	4A	250V	1
GSD5	GSD-V5	5A	250V	1
GSD6-3/10	GSD-V6-3/10	6-3/10A	250V	1
GSD8	GSD-V8	8A	250V	1
GSD10	GSD-V10	10A	250V	1

1. 250VAC @ 1500A I.R.

* IEC Standards for 5x20mm fuses do not include ratings above 6.3 amperes.

CATALOG NUMBER	AXIAL LEAD CAT. NO	AMPERE RATING	VOLTS	IR
GSF2/10	GSF-V2/10	2/10A	250V	1
GSF1/4	GSF-V1/4	1/4A	250V	1
GSF315/1000	GSF-V315/1000	315/1000A	250V	1
GSF4/10	GSF-V4/10	4/10A	250V	1
GSF1/2	GSF-V1/2	1/2A	250V	1
GSF630/1000	GSF-V630/1000	630/1000A	250V	1
GSF8/10	GSF-V8/10	8/10A	250V	1
GSF1	GSF-V1	1A	250V	1
GSF1-1/4	GSF-V1-1/4	1-1/4A	250V	1
GSF1-6/10	GSF-V1-6/10	1-6/10A	250V	1
GSF2	GSF-V2	2A	250V	1
GSF2-1/2	GSF-V2-1/2	2-1/2A	250V	1
GSF3-15/100	GSF-V3-15/100	3-15/100A	250V	1
GSF4	GSF-V4	4A	250V	1
GSF5	GSF-V5	5A	250V	1
GSF6-3/10	GSF-V6-3/10	6-3/10A	250V	1
GSF8	GSF-V8	8A	250V	1
GSF10	GSF-V10	10A	250V	1

1. 250VAC @ 1500A I.R.

* IEC Standards for 5x20mm fuses do not include ratings above 6.3 amperes.