



Part Number: 8918

Lead Wire, #18 Str TC, PVC Ins, AWM 1015 CSA TYPE TEW

[Request Sample](#)

Product Description

Low Temp Plastic Lead Wire, 18AWG (16x30) Tinned Copper, PVC Insulation, AWM 1015 CSA TYPE TEW JQA-F 600V 105C

Technical Specifications

Physical Characteristics (Overall)

Conductor

AWG	Stranding	Material	No. of Conductors
18	16x30	TC - Tinned Copper	1

Conductor Count:	1
Conductor Size:	18 AWG

Insulation

Material	Nominal Diameter	Nominal Wall Thickness	Min. Average Wall Thickness
PVC - Polyvinyl Chloride	0.11 in	.0325 in	0.03 in

Outer Jacket Material

Material	Nominal Diameter
No Jacket	0.11 in

Electrical Characteristics

Conductor DCR

Nominal Conductor DCR
5.9 Ohm/1000ft

Current

Element	Max. Recommended Current [A]
Single conductor in free air @ 30C ambient	Single conductor in free air @ 30C ambient 20 amps

Voltage

UL Voltage Rating
600 V

Temperature Range

UL Temp Rating:	105°C
-----------------	-------

Mechanical Characteristics

Bulk Cable Weight:	10 lbs/1000ft
--------------------	---------------

Standards

NEC/(UL) Specification:	MTW
UL AWM Style:	1015, 1230
CSA Rating:	600 V, 105°C
CSA AWM Specification:	AWM I A/B

CSA Type:	AWM I A/B or TEW
Military Specification:	N/A

Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2005-07-01
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

Flammability, LSOH, Toxicity Testing

UL Flammability:	VW-1
CSA Flammability:	FT1
UL voltage rating:	600 V RMS

Plenum/Non-Plenum

Plenum (Y/N):	No
---------------	----

Part Number

Variants

Item #	Color	UPC	Length	Footnote
8918 010100	Black	612825219989	100 ft	
8918 0101000	Black	612825219996	1,000 ft	P
8918 0105000	Black	612825220008	5,000 ft	C
8918 013100	Blue, Dark	612825220060	100 ft	
8918 0131000	Blue, Dark	612825220077	1,000 ft	P
8918 0135000	Blue, Dark	612825220084	5,000 ft	C
8918 001100	Brown	612825219606	100 ft	
8918 0011000	Brown	612825219613	1,000 ft	P
8918 0081000	Gray	612825219866	1,000 ft	P
8918 0085000	Gray	612825219873	5,000 ft	P
8918 005100	Green, Dark	612825219804	100 ft	
8918 0051000	Green, Dark	612825219811	1,000 ft	P
8918 0055000	Green, Dark		5,000 ft	P
8918 189100	Green, Yellow Stripe	612825220107	100 ft	A
8918 1891000	Green, Yellow Stripe	612825348030	1,000 ft	A
8918 003100	Orange	612825219699	100 ft	
8918 0031000	Orange	612825219705	1,000 ft	P
8918 002100	Red	612825219637	100 ft	
8918 0021000	Red	612825219644	1,000 ft	P
8918 0025000	Red	612825219651	5,000 ft	C
8918 0071000	Violet	612825219842	1,000 ft	P
8918 009100	White	612825219903	100 ft	
8918 0091000	White	612825219910	1,000 ft	P
8918 0095000	White	612825219927	5,000 ft	C
8918 004100	Yellow	612825219743	100 ft	
8918 0041000	Yellow	612825219750	1,000 ft	P
8918 0045000	Yellow	612825219767	5,000 ft	C

Footnote:	C - CRATE REEL PUT-UP.
Footnote:	P - STRIPE COLORS ON STOCK SOLID COLORS. STRIPING ADDER OF \$8.00/M= FOR 1 OR 2 STRIPES. 10,000' MINIMUM ORDER FOR COLOR COMBINATION. PUT-UP WILL BE SUBJECT TO TWO PIECES (+ OR -) 10% PER SPOOL, WITH A MINIMUM LENGTH OF 100'.

© 2019 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.