

## Insertion bridge - EB 10- 6 - 0201139

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Insertion bridge, pitch: 6.2 mm, number of positions: 10, color: gray

RoHS

### Key Commercial Data

|                                      |   |
|--------------------------------------|---|
| Packing unit                         | 1 pc  |
| Minimum order quantity               | 10 pc   |
| GTIN                                 | <br>4 017918 098124 |
| GTIN                                 | 4017918098124   |
| Weight per Piece (excluding packing) | 6.080 g   |
| Custom tariff number                 | 85366990  |
| Country of origin                    | Poland  |

### Technical data

#### Technical data

|  |                      |
|--|----------------------|
| Color                                  | gray                 |
| Material                               | CuZn (nickel-plated) |
| Number of positions                    | 10                   |
| Pitch                                  | 6.2 mm               |
| Flammability rating according to UL 94 | V2                   |

#### Ambient conditions

|  |   |
|--|---|
| Operating temperature                    | -60 °C ... 105 °C (max. short-term operating temperature 125°C)           |
| Ambient temperature (storage/transport)  | -25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C) |
| Permissible humidity (storage/transport) | 30 % ... 70 %   |

# Insertion bridge - EB 10- 6 - 0201139

## Technical data

### Ambient conditions

|                                 |                 |
|---------------------------------|-----------------|
| Ambient temperature (assembly)  | -5 °C ... 70 °C |
| Ambient temperature (actuation) | -5 °C ... 70 °C |

### Standards and Regulations

|  |    |
|--|----|
| Flammability rating according to UL 94 | V2 |
|--|----|

### Environmental Product Compliance

|            |   |
|------------|---|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
|            | No hazardous substances above threshold values          |

## Classifications

### eCl@ss

|               |          |
|---------------|----------|
| eCl@ss 10.0.1 | 27141140 |
| eCl@ss 11.0   | 27141140 |
| eCl@ss 4.0    | 27141100 |
| eCl@ss 4.1    | 27141100 |
| eCl@ss 5.0    | 27141100 |
| eCl@ss 5.1    | 27141100 |
| eCl@ss 6.0    | 27141100 |
| eCl@ss 7.0    | 27141140 |
| eCl@ss 9.0    | 27141140 |

### ETIM

|          |          |
|----------|----------|
| ETIM 2.0 | EC000489 |
| ETIM 3.0 | EC000489 |
| ETIM 4.0 | EC000489 |
| ETIM 6.0 | EC000489 |
| ETIM 7.0 | EC000489 |

### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 30211829 |
| UNSPSC 7.0901 | 39121426 |
| UNSPSC 11     | 39121426 |
| UNSPSC 12.01  | 39121426 |
| UNSPSC 13.2   | 39121426 |
| UNSPSC 18.0   | 39121426 |
| UNSPSC 19.0   | 39121426 |
| UNSPSC 20.0   | 39121426 |

## Insertion bridge - EB 10- 6 - 0201139

### Classifications

#### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 39121426 |
|-------------|----------|