


Type	V _R -V _{RM} max (V)	I _O max (mA)	V _F / I _F max (V) (mA)	I _R / V _R max (nA) (V)	I _R / V _R T _{amb} 150°C max (μA) (V)	C max (pF)	t _{rr} / I _F max (ns) (mA)	Case
------	---	-------------------------------	--	--	--	------------------	--	------

high speed switching


T_{amb} = 25°C

commutation rapide

1N 482	30- 40	100	1,1	100	250	30	30				
1N 662	50-100	75	1	10	1000	10	20 (1)	10	3		
1N 662 A	50-100	75	1	10	1000	10	20 (1)	10	3		
1N 914	75-100	75	1	10	25	20	50	20	4	4	10
1N 914 A	75-100	75	1	20	25	20	50	20	4	4	10
1N 914 B	75-100	75	1	100	25	20	50	20	4	4	10
1N 916	75-100	75	1	10	25	20	50	20	2	4	10
1N 916 A	75-100	75	1	20	25	20	50	20	2	4	10
1N 930	50- 75	75	1	20	100	50					
1N 916 B	75-100	75	1	30	25	20	50	20	2	4	10
1N 3062	75- 50	75	1	20	100	50	100	50	1	2	10
1N 3063	50- 75	75	0,85	10	100	50	100	50	2	4	10
1N 3064	50- 75	75	1	10	100	50	100	50	2	4	10
1N 3604	50- 75	75	1	50	50	50	50	50	2	2	10
1N 3605	35- 40	75	0,88	20	50	50	50	30	2	2	10
1N 3606	50- 75	75	0,88	20	50	50	50	50	2	2	10
1N 4009	25- 35	75	1	30	100	25	100	25	4	2	10
BAY 38	50	75	1	50	50	50	50	50	2	4	10
BAY 43	40- 80	200	1	200	50	40	30	40	5	15	200
BAY 63	50	100	1	100	100	50	100	50	4	2	10
BAY 71	35- 50	75	1	20	100	35			2	2	10
▲Δ1N 4148	75-100	75	1	10	25	20	50	20	4	4	10
▲Δ1N 4149	75-100	75	1	10	25	20	50	20	2	4	10
▲Δ1N 4151	50- 75	75	1	50	50	50	50	50	2	4	10
1N 4152	30- 40	75	0,88	20	50	30	50	30	2	4	10
1N 4153	50- 75	75	0,88	20	50	50	50	50	2	4	10
1N 4154	25- 35	75	1	30	100	25	100	25	4	4	10
1N 4305	50- 75	150	0,85	10	100	50	100	50	2	2	10
1N 4444	50- 70	200	1	100	50	50	50	50	2	7	10
▲Δ1N 4446	75-100	75	1	20	25	20	50	20	4	4	10
▲Δ1N 4447	75-100	75	1	20	25	20	50	20	2	4	10
1N 3731	50-100	100	1	100	50	50	50	50	2	3	10
▲Δ1N 4448	75-100	75	1	100	25	20	50	20	4	4	10
▲Δ1N 4449	75-100	75	1	30	100	20	50	20	2	4	10
1N 4454	50- 75	75	1	10	100	50	100	50	2	2	10
34 P 4	20- 25	75	1	15	30	10			4	10	10
35 P 4	45- 50	75	1	20	10	20			2		
36 P 4	90-100	75	1	10	60	50			2	10	10
37 P 4	45- 50	75	1	20	10	20			2	6	10
BAV 54-30	30- 30	150	1	10	200	20			4	4	10
BAV 54-70	70- 70	150	1	10	200	40			4	4	10
BAV 54-100	100-100	150	1	10	200	60			4	4	10
BAW 75	25- 35	75	1	30	100	25	100	25	4	4	10
BAW 76	50- 75	115	1	100	100	50	100	50	2	4	10
BAX 13	50- 50	75	1	20	200	50	25	50	3	4	10
BAX 84	20- 50	75	1	40	10	20			2	10	10
BAY 67	35- 35	130	1	200	100	35	50	35	1,5		
BAY 68	25- 35	75	1	100	100	25	100	30	5	10	10
SFD 43	25- 30	75	1,1	10	200	10			4	4	10
1N 4531 (2)	75-100	150	1	10	25	20	50	20	4	4	10
ESM 523	75	100	1	100	25	20	10 (1)	20	4	4	10



DO 7*
(CB-26)



CB-127



CB-165
Microdiode
Scale : 3/1
Echelle : 3/1

(1) : T_{amb} = 100°C

Δ: Devices under CCQ/CCT
Dispositifs soumis au CCQ/CCT

* Available on request in CB-127 case.

Designation : 1N...DHD or BA...DHD.

* Livrable sur demande en boîtier CB-127.

Appellation commerciale : 1N...DHD ou BA...DHD.

(2) : DO 34 case (CB-104)
Boîtier DO 34 (CB-104)

▲: Devices under CCQ/CECC
Dispositifs soumis au CCQ/CECC