


Hi-Rel PLANAR POWER — 5 AMP PNP



10

TYPE	CASE	BREAKDOWN VOLTAGES			h _{FE}				CUTOFF CURRENT	
		V _{CB}	V _{CE}	V _{EB}	@ V _{CE}	@ I _C A	Min.	Max.	@ V _{CB}	(μA)
2N 3202	TO-5	-40	-40	-10	-2.0	-1.0	20	60	-30	-75
2N 3203	TO-5	-60	-60	-10	-2.0	-1.0	20	60	-40	-75
2N 3204	TO-5	-80	-80	-10	-2.0	-1.0	20	60	-60	-75
2N 3719	TO-5	-40	-40	-4.0	-1.5	-1.0	25	180	-30	-10
2N 3720	TO-5	-60	-60	-4.0	-1.5	-1.0	25	180	-40	-10
2N 3775	TO-5	-60	-60	-8	-2.0	-0.2	20	60	-60	-500
2N 3776	TO-5	-80	-80	-8	-2.0	-0.2	20	60	-80	-500
2N 3777	TO-5	-100	-100	-8	-2.0	-0.2	20	60	-100	-500
2N 3778	TO-5	-40	-40	-8	-2.0	-0.2	10	40	-40	-500
2N 3867	TO-5	-40	-40	-4	-3.0	-2.5	25	—	-40	-150
2N 3868	TO-5	-60	-60	-4	-3.0	-2.5	20	—	-60	-150
2N 4901	TO-3	-40	-40	-5.0	-2.0	-1.0	20	80	-30	-100
2N 4902	TO-3	-60	-60	-5.0	-2.0	-1.0	20	80	-40	-100
2N 4903	TO-3	-80	-80	-5.0	-2.0	-1.0	20	80	-60	-100
2N 4904	TO-3	-40	-40	-5.0	-2.0	-2.5	25	100	-30	-100
2N 4905	TO-3	-60	-60	-5.0	-2.0	-2.5	25	100	-40	-100
2N 4906	TO-3	-80	-80	-5.0	-2.0	-2.5	25	100	-60	-100
2N 4907	TO-3	-40	-40	-5.0	-4.0	-4.0	20	80	-30	-2.0mA
2N 4908	TO-3	-60	-60	-5.0	-4.0	-4.0	20	80	-40	-2.0mA
2N 4909	TO-3	-80	-80	-5.0	-4.0	-4.0	20	80	-60	-2.0mA
2N 4999	TO-111	-100	-80	-5.5	-5.0	-1.0	30	90	-100	-1.0mA
2N 5001	TO-59	-100	-80	-5.5	-5.0	-1.0	70	200	-100	-1.0mA
2N 5003	TO-59	-100	-80	-5.5	-5.0	-2.5	30	90	-100	-1mA
2N 5005	TO-59	-100	-80	-5.5	-5.0	-2.5	70	200	-100	-1mA
2N 5147	TO-5	-100	-80	-5.5	-5.0	-1.0	30	90	-100	-1.0mA
2N 5149	TO-5	-100	-80	-5.5	-5.0	-1.0	70	120	-100	-1.0mA
2N 5151	TO-39	-100	-80	-5.5	-5.0	-2.5	30	90	-100	-1mA
2N 5153	TO-39	-100	-80	-5.5	-5.0	-2.5	70	200	-100	-1mA
2N 5286	TO-59	-100	-100	-5.5	-5.0	-2.5	30	90	-100	-1mA
2N 5287	TO-59	-100	-100	-5.5	-5.0	-2.5	70	200	-100	-1mA
2N 5333	TO-5	-100	-80	-6	-4.0	-1.0	30	120	-100	-10
2N 5384	TO-111	-100	-80	-6	-4.0	-2.0	20	80	-100	-10
2N 5385	TO-111	-100	-80	-6	-4.0	-2.0	20	80	-100	-10
2N 5597	TO-66	-80	-60	-5.5	-5.0	-1.0	70	200	-80	-1.0mA
2N 5599	TO-66	-100	-80	-5.5	-5.0	-1.0	30	90	-100	-1.0mA
2N 5601	TO-66	-100	-80	-5.5	-5.0	-1.0	70	200	-100	-1.0mA
2N 5603	TO-66	-120	-100	-5.5	-5.0	-1.0	30	90	-120	-1.0mA
2N 5605	TO-66	-80	-60	-5.5	-5.0	-2.5	70	200	-80	-1.0mA
2N 5607	TO-66	-100	-80	-5.5	-5.0	-2.5	30	90	-100	-1.0mA
2N 5609	TO-66	-100	-80	-5.5	-5.0	-2.5	70	200	-100	-1.0mA
2N 5611	TO-66	-120	-100	-5.5	-5.0	-2.5	30	90	-120	-1.0mA

CONSULT FACTORY FOR DETAILED SPECIFICATIONS.