



[Home](#) | [Sign In](#) | [Contact Us](#)

SEARCH

Go



Standard D (Machined)

PART NUMBER: DAMM15S



Where Sold	Americas, Asia Pacific, Europe
Product Group	D-Subminiature
Product Sub-Family	D-Sub Standard
Component Type	Connector
Application Type	Military/High Reliability
Cable or PC Board	Cable
Gender	Receptacle
Number of Signal Pins	15
Number of Size 8 contacts	0
Straight or Right Angle	Straight
Contact Plating	50 micro inches Gold over Nickel
Shell Plating	Yellow Chromate over Zinc
Hardware	3,05 (.120) Through Holes
Contact Termination	Solder Cup
Shell Size	DA
Temperature Rating	-55°C to +125°C
Current Capacity	5 A
Contact Resistance	8 milli ohms max.

- Sales Support
- Ask a Specialist
- Product Home
- Stock Check
- Dimensional Drawing

PRINTABLE PAGE

Dielectric Withstanding Voltage	1250 V AC at Sea Level
Reference Industry Specifications	Mil-PRF-24308
Insulator Material	Polyester
Contact Material	Copper Alloy
Shell Material	Steel

[Home](#)|[About ITT](#)|[Products](#)|[Design Center](#)|[Literature](#)|[News & Events](#)|[Search Tools](#)|[Global Sales Support](#)
© *ITT Corporation. All rights reserved.* [Legal Disclaimer](#)|[Privacy Policy](#)|[General Terms of Sale](#)
[Channel Partners Sign-In](#)