

Power Rectifier Diodes

Type	Construction	Peak Inverse Voltage	Max. Rect. Current (A)	Max. Forward Voltage Drop		Max. Reverse Current		Connections				
				Volts	at Amps	μA	at Volts					
<b>R.C.A. (Continued)</b>												
<i>Current Types (Continued)</i>												
D1201M (44005)	Silicon diffused junction	400	1	1.1	1	—	—	A1				
D1201N (44006)		800	1	1.1	1	—	—	A1				
D1201P (44007)		1,000	1	1.1	1	—	—	A1				
D2101S (40892)		700	1	1.5	4	—	—	A3				
D2103S (40891)		700	3	1.4	4	—	—	A3				
D2103SF (40890)		750	3	1.4	4	—	—	A3				
D2201A (44934)		100	1.5	1.9	4	—	—	A1				
D2201B (44935)		200	1.5	1.9	4	—	—	A1				
D2201D (44936)		400	1.5	1.9	4	—	—	A1				
D2201F (44933)		50	1.5	1.9	4	—	—	A1				
D2201M (44937)		600	1.5	1.9	4	—	—	A1				
D2201N (44938)		800	1.5	1.9	4	—	—	A1				
D2540A (40957)		100	60	1.8	100	—	—	S2				
D2540B (40958)		200	60	1.8	100	—	—	S2				
D2540D (40959)		400	60	1.8	100	—	—	S2				
D2540F (40956)		50	60	1.8	100	—	—	S2				
D2540M (40960)		600	60	1.8	100	—	—	S2				
D2600EF (40644)		550	1	1.6	0.02	—	—	A10				
D2601A		100	1.5	1.9	4	—	—	A10				
D2601B (TA7892)		200	1.5	1.9	4	—	—	A10				
D2601D (TA7893)		400	1.5	1.9	4	—	—	A10				
D2601DF (40643)		450	1.5	1.9	4	—	—	A10				
D2601EF (40642)		550	1.5	1.9	4	—	—	A10				
D2601F		50	1.5	1.9	4	—	—	A10				
D2601M (TA7894)		600	1.5	1.9	4	—	—	A10				
D2601N (TA7895)		800	1.5	1.9	4	—	—	A10				
TAD2201D		400	1	1.5	4	—	—	A1				
TAD2201G		150	1.8	1.6	4	—	—	A1				
TAD2201MF		650	1	1.5	4	—	—	A1				
1N248C		50	20	0.6	20	—	—	S2				
1N249C		100	20	0.6	20	—	—	S2				
1N250C		200	20	0.6	20	—	—	S2				
1N440B		100	0.75	1.5	0.75	—	—	A10				
1N441B		200	0.75	1.5	0.75	—	—	A10				
1N442B		300	0.75	1.5	0.75	—	—	A10				
1N443B		400	0.75	1.5	0.75	—	—	A10				
1N444B		500	0.65	1.5	0.65	—	—	A10				
1N445B		600	0.65	1.5	0.65	—	—	A10				
1N536		50	0.75	1.1	0.5	—	—	A10				
1N537		100	0.75	1.1	0.5	—	—	A10				
1N538		200	0.75	1.1	0.5	—	—	A10				
1N539		300	0.75	1.1	0.5	—	—	A10				
1N540		400	0.75	1.1	0.5	—	—	A10				
1N547		600	0.75	1.2	0.5	—	—	A10				
1N1095		500	0.75	1.2	0.5	—	—	A10				
1N1183A		50	40	0.65	40	—	—	A1				
1N1184A		100	40	0.65	40	—	—	A1				
1N1186A		200	40	0.65	40	—	—	A1				
1N1187A		300	40	0.65	40	—	—	A1				
1N1188A		400	40	0.65	40	—	—	A1				
1N1189A		500	40	0.65	40	—	—	A1				
1N1190A		600	40	0.65	40	—	—	A1				
1N1195A		300	20	0.6	20	—	—	A1				
1N1196A		400	20	0.6	20	—	—	A1				
1N1197A		500	20	0.6	20	—	—	A1				
1N1198A		600	20	0.6	20	—	—	A1				
1N1199A		50	12	0.55	12	—	—	S2				
1N1200A		100	12	0.55	12	—	—	S2				
1N1202A		200	12	0.55	12	—	—	S2				
1N1203A		300	12	0.55	12	—	—	S2				
1N1204A		400	12	0.55	12	—	—	S2				
1N1205A		500	12	0.55	12	—	—	S2				