

## Modular Potentiometers with Cermet (P11) or Conductive Plastic Elements (PA11)



### FEATURES

- CECC 41300
- GAM T1
- P11 version for industrial and military applications
- PA11 version for professional audio applications
- Trimmer version T11/TA11 (see document No. 51021)
- Miniature module size: 12.5 mm square - low current compatibility
- Five shaft diameters and 12 terminal styles
- Multiple assemblies - up to seven modules
- Shaft and panel sealed version
- Up to twenty-one indent positions
- Switch modules
- Concentric shafts
- Motorized version
- Custom designs



VERSATILE	MODULAR	COMPACT	ROBUST
-----------	---------	---------	--------


ELECTRICAL SPECIFICATIONS			PA11	P11
Resistive Element			Conductive plastic	Cermet
Electrical Travel			270° ± 10°	270° ± 10°
Resistance Range*	Linear Law		1 kΩ to 1 MΩ	10 Ω to 10 MΩ
	Non Linear Law		470 Ω to 500 kΩ	100 Ω to 2.2 MΩ
Tolerance	Standard		± 20 %	± 20 %
	On request		-	± 5 % or ± 10 %
Power Rating	Linear Law		0.5 W at + 70 °C	1 W at + 70 °C
	Non linear Laws		0.25 W at + 70 °C	0.5 W at + 70 °C
	Multiple Assemblies		0.25 W at + 70 °C per module	0.5 W at + 70 °C per module
Temperature Coefficient (Typical)			± 500 ppm/°C	± 100 ppm/°C (R ≥ 100 Ω)
Limiting Element Voltage			350 V	350 V
Contact Resistance Variation	Linear Law		1 %	2 % or 3 Ω
End Resistance (Typical)			2 Ω	2 Ω
Independent Linearity (Typical)	Linear Law		± 5 %	± 5 %
Insulation Resistance			10 <sup>6</sup> MΩ min.	10 <sup>6</sup> MΩ min.
Dielectric Strength			1500 V <sub>RMS</sub> min.	1500 V <sub>RMS</sub> min.
Attenuation			90 dB max. and 0.05 dB min.	-
Mechanical Rotational Life			50 000 cycles	50 000 cycles

\* Consult Vishay Sfernice for other ohmic values

### MECHANICAL SPECIFICATIONS PA11 AND P11

- Mechanical Travel:** 300° ± 5°
- Operating Torque, Single and Dual Assemblies:**
- 3 mm, 4 mm (1/8") dia. Shafts: 0.5 to 1.3 Ncm max. (0.7 to 1.8 oz-inch max.)
  - 6 mm (1/4") dia. Shafts: 0.7 to 1.5 Ncm max. (1 to 2.1 oz-inch max.)
- Three to Seven Modules (per module):** 0.2 to 0.3 Ncm max. (0.3 to 0.45 oz-inch max.)
- End Stop Torque:**
- 3 mm, 4 mm (1/8") dia. Shafts: 25 Ncm max. (2.1 lb-inch max.)
  - 6 mm (1/4") dia. Shafts: 80 Ncm max. (6.8 lb-inch max.)
- Tightening Torque:**
- 6 mm, 7 mm (1/4") dia. bushings: 150 Ncm max. (13 lb-inch max.)
  - 10 mm (3/8") dia. bushings: 250 Ncm max. (21 lb-inch max.)
- Weight:** 7 g to 9 g per module (0.25 to 0.32 oz)

### VARIATION LAWS






**Modular Potentiometers with Cermet (P11) or  
Conductive Plastic Elements (PA11)**


Vishay Sfernice

**DIMENSIONS** in millimeters [inches]

**PCB PIN OUT A - A<sub>1</sub> - A<sub>2</sub>/X - X<sub>1</sub> - X<sub>2</sub>/Z - Z<sub>1</sub> - Z<sub>2</sub>/W - W<sub>1</sub> - W<sub>2</sub>**




**SOLDER LUGS Y**




**PANEL AND SHAFT SEALED  
TP/QP/VP/2P/7P**


All models have same bushing DIA 8 mm - L 8 mm




**PANEL CUT OUT**



**CIRCUIT DIAGRAM**




**CONCENTRIC SHAFT**




The position of each module is free

**P11/PA11 71**    **P11/PA11 71H**  
**P11/PA11 72**    **P11/PA11 72H with spindle baking nut**



**SWITCH: MOMENTARY PUSH OR PUSH-PUSH**



Shafts	T	Q	V	CC	7	71	72	2	0	77		
	dimensions mm ± 0.5				dimensions inches ± (0.01)							
A Shafts Ø	3	4	6	3/6	1/8"	1/8"	1/8"	1/4"	1/8"	1/4"	0.07	1/8"
B Bushing Ø	6	7	10	10	1/4"	1/4"	1/4"	3/8"	3/8"	1/4"		
C L	8	8	9.5	9.5	1/4"	3/8"	1/2"	3/8"	3/8"	1/4"		
J version Y, X, X <sub>1</sub> , X <sub>2</sub>	5	5	7	7	0.200	0.200	0.200	0.278	0.278	0.200		
K	9.1	9.1	11.1	-	0.357	0.357	0.357	0.436	-	-		
E version Z	1.8	1.8	3.8	3.8	0.071	0.071	0.071	0.150	0.150	0.071		
E version	1.6	1.6	3.6	3.6	0.063	0.063	0.063	0.14	0.14	0.063		
F	version Z : 5.08 (0.200)				versions A- A <sub>1</sub> -A <sub>2</sub> -Z <sub>1</sub> -Z <sub>2</sub> : 3.81 (0.150)							
G Panel	5.2	6.2	8.2	8.2	0.197	0.197	0.197	0.323	.323	0.197		
H Cutout Ø	6.5	7.5	10.5	10.5	0.268	0.268	0.268	0.394	0.394	0.268		
a	variable	5.08 (0.200)			7.62 (0.300)			10.16 (0.400)				
Thread	M 0.75				32 threads/inch							
Nut	8	10	12	12	0.313	0.313	0.313	0.500	0.500	0.313		
Shaft lengths L	Measurement from the mounting face, see ordering procedures											

# P11, PA11



Vishay Sfernice


Modular Potentiometers with Cermet (P11) or  
Conductive Plastic Elements (PA11)

## ENVIRONMENTAL SPECIFICATIONS

	PA11	P11
Operating Temperature Range	- 55 °C + 125 °C	- 55 °C + 125 °C
Climatic Category	55/125/21	55/125/56
Sealing	IP64	IP64
Storage Temperature	- 55 °C + 125 °C	- 55 °C + 150 °C

STANDARD RESISTANCE VALUES	P11 CERMET						PA11 CONDUCTIVE PLASTIC LINEAR LAW			CT		
	LINEAR LAW			NON LINEAR LAW			MAX. POWER AT 70 °C	MAX. WORKING VOLTAGE	MAX. CUR. THROUGH WIPER	- 55 °C	+ 125 °C	
	MAX. POWER AT 70 °C	MAX. WORKING VOLTAGE	MAX. CUR. THROUGH WIPER	MAX. POWER AT 70 °C	MAX. WORKING VOLTAGE	MAX. CUR. THROUGH WIPER				P11	PA11	
	Ω	W	V	mA	W	V	mA	W	V	mA	ppm/°C	
22	1	4.69	213.2								± 200	
47		6.85	145.8									
100		10	100									
200		14.8	67.4	0.5								
470		21.6	46.1		15.3	32.7						
1k		31.6	31.6		22.4	22.4	0.5	22.4	22.4			
2.2k		46.9	21.3		33.2	15.1		33.2	15.1			
4.7k		63.5	14.5		48.5	10.3		48.5	10.3			
10k		100	10		79.7	7.07		79.7	7.07		± 100	± 1000
22k		148.3	6.7		105	4.77		105	4.77			
47k		216.7	4.6		153	3.26		153	3.26			
100k	1	316.2	3.16	0.5	224	2.24	0.5	224	2.24			
220k	0.56	350	1.59	0.26	332	1.51	0.5	332	1.51			
470k	0.26	350	0.75	0.12	350	0.74	0.26	350	0.74			
1M	0.12	350	0.35		350	0.35						
2.2M	0.05	350	0.16									
4.7M	0.02	350	0.07									

## POWER RATING CHART



## MULTIPLE ASSEMBLIES

Standard assemblies can comprise up to 7 modules in addition to the shaft and bushing module.

Detents module (CV)


Switch modules (RS or RSI)

Potentiometer modules

Spacer module (EV) to increase the distance between rows of pins from 5.06 mm (0.200) to 10.16 mm (0.400).

Screening module, with ground terminal.

The position of each module is free except the push/push, momentary push and motor which has to be the last module.

**LINEARITY - CONFORMITY**



The independent linearity (conformity for the non linear laws) is the maximum gap  $\Delta V$  between the actual variation curve and the theoretical variation curve the nearest to it. The linearity and the conformity are expressed in percentage of the total applied voltage  $E$

$$\text{linearity conformity} = \frac{\pm \Delta V \text{ max}}{E}$$

They are measured over 90 % of actual electrical travel (centered).

On request linearity can be guaranteed in linear law.

For example: linearity  $\pm 2\%$  + J 145 option (see ordering procedure).

**INTERLINEARITY - INTERCONFORMITY**


It is the maximum deviation between the actual voltage outputs of 2 or more pot modules in the same assembly. It is expressed as a percentage of the total applied voltage, or preferably in dB attenuation.

Interlinearity is measured between 2 pot modules, over 10 to 90 % of the attenuation.

The interlinearity or interconformity is expressed as a percentage of the total applied voltage :

$$I\% = \frac{|C|}{E}$$

Or in decibels by comparison between outputs  $V_1$  and  $V_2$

$$I \text{ dB} = 20 \log \frac{V_1}{V_2}$$

PERFORMANCE				
TESTS	CONDITIONS	TYPICAL VALUES AND DRIFTS		
			P11 CERMET	PA11 CONDUCTIVE PLASTIC
Load Life	1000 h at + 70 °C (90'/30')	total resistance shift	$\pm 2\%$	$\pm 10\%$
		contact resistance variation	$\pm 4\%$	$\pm 5\%$
Temperature Cycle	5 cycles - 55 °C to 125 °C	total resistance shift	$\pm 0.2\%$	$\pm 0.5\%$ typical
Moisture	+ 40 °C 93 % relative humidity	total resistance shift insulation resistance	56 days $\pm 2\%$ > 1000 M $\Omega$	21 days $\pm 5\%$ > 10 M $\Omega$
Rotational Life	P11/PA11: 50 000 cycles	total resistance shift contact resistance variation	$\pm 5\%$ $\pm 5\%$	$\pm 6\%$ $\pm 2\%$
Climatic Sequence	Dry heat at + 125 °C/Damp heat Cold - 55 °C/Damp Heat 5 cycles	total resistance shift	$\pm 1\%$	-
Shock	50 G 11 ms 3 shocks - 3 directions	total resistance shift resistance setting change	$\pm 0.2\%$ $\pm 0.5\%$	$\pm 0.2\%$ $\pm 0.5\%$ typical
Vibration	10 - 55 Hz 0.75 mm or 10 G 6 hours	total resistance shift voltage setting change	$\pm 0.2\%$ $\pm 0.5\%$ typical	$\pm 0.2\%$ $\pm 0.5\%$ typical

## OPTIONS

### MODULES : RS ON/OFF SWITCH RSI CHANGEOVER SWITCH

The position of each module is free.

RS and RSI rotary switches are housed in a standard P11 module size 12.7 x 12.7 x 5.08 mm (0.5" x 0.5" x 0.2"). They have the same terminal styles as the assembled electrical modules.

**CAUTION:** Because of the switch actuation travel, the potentiometer total electrical travel is reduced to  $240^\circ \pm 10^\circ$

Switch actuation is described as seen from the shaft end.

D: means actuation in maximum CCW position

F: means actuation in maximum CW position

The switch actuation travel is  $25^\circ$  with a total mechanical travel of  $300^\circ \pm 5^\circ$ .

### MODULES : PUSH/PUSH SWITCH RSPP MOMENTARY/PUSH SWITCH RSMP

The switches are manufactured by ITT, F.U. series (NE18 series available on request).

They have to be the last element of potentiometer and are linked to electrical module by an interface.

RSPP and RSMP switches are available only with P11/PA11 T-Q or 7 series not with P11/PA11 V or 2 series.

Options :

2 reversing switches F2 4 reversing switches F4

6 reversing switches F6 8 reversing switches F8

Available with shafts R (T), G (Q), CR (7) others shafts on request.

Not available with panel sealed option.

Number of modules before the switch limited to 3 modules.


### VALLEY DETENTS

The valley detents mechanism is housed in a standard P11 module. Up to 21 detents position available.


Count detents as follows : 1 for CCW position, 1 for full CW position, plus the other positions forming **equal resistance increments** (linear taper) - **not equal angles**.

Available now : CVID - CVIF - CVIM

CV3 - CV11 - CV21



### SWITCH MODULES



### RSD SINGLE POLE SWITCH, NORMALLY OPEN

In full CCW position, the contact between 1 and 3 is open. It is made at the beginning of the travel in CW direction.

### RSF SINGLE POLE SWITCH, NORMALLY OPEN

In full CW position, the contact between 1 and 3 is open. It is made at the beginning of the travel in CCW direction.

### RSID SINGLE POLE CHANGEOVER

In full CCW position, the contact is made between 3 and 2 and open between 3 and 1. Switch actuation (CW direction) reverses these positions.

### RSIF SINGLE POLE CHANGEOVER

In full CW position, the contact is made between 1 and 2 and open between 1 and 3. Switch actuation (CCW direction) reverses these positions.

### RSPF F2 : PUSH/PUSH SWITCH WITH TWO REVERSING SWITCHES

Idle position : the contact is made between 1 and 2 and a and b. It is open between 2 and 3 and b and c.

Pushed position: the contact is made between 2 and 3 and b and c. It is open between 1 and 2 and a and b.


Not available on P11V and P11-2.

On request for P11Q and P11-7.

### SWITCH SPECIFICATIONS

MODEL	RS - RSI	F2 to F8
Switching Power max.	62.5 VA $\cup$ 15 VA =	50 VA $\cup$
Switching Current max.	0.25 A 250 V $\cup$ 0.5 A 30 V =	0.5 A $\cup$
Max. Current Through Element	2 A	2 A
Contact Resistance	30 m $\Omega$	100 m $\Omega$
Dielectric Strength	Terminal to Terminal	1000 V <sub>RMS</sub>
	Terminal to Bushing	2000 V <sub>RMS</sub>
Max. Voltage Operation	250 V $\cup$ 30 V =	250 V $\cup$
Insulation Resistance Between Contacts	10 <sup>6</sup> M $\Omega$	10 <sup>3</sup> M $\Omega$
Life at P max.	10 000 actuations	100 000 actuations
Minimal Travel	25°	3.3 mm to 4.7 mm
Operating Temperature	- 40 °C to + 85 °C	- 20 °C + 70 °C

### ELECTRICAL DIAGRAM






**CENTER TAP "J"**

The extra terminal is a solder lug connected at 50 % of electrical travel and situated in the potentiometer module opposite the terminals.

Center tap short circuit 11° of travel.



**SHAFTS** (see Ordering Information)

The shaft lengths are always measured from the mounting face.

Standard shafts are designed by a letter code (one or two digits). Shafts slots are aligned to ± 10° of the wiper position.

**CONCENTRIC SHAFTS**

The CC or 0 or 77 concentric shaft versions allies the total flexibility of the P11/PA11 modular system to the advantage of having two separate shafts.

The outer 6 mm or 1/4" or 1/8" dia. shaft drives the modules situated immediately behind the panel, before the spacer module.

The inner 3 mm or 1/8" or 0.07" dia. shaft drives the modules situated after the spacer module.

Spacer is available with a choice of two spacer thickness :


5.08 mm designations: CC, 0, 77

2.54 mm designations: CC-3, 0-3, and 77-3. See dimensional drawings on second page of this data sheet

**CUSTOM SHAFTS**

When special shafts are required - flat, threaded ends, special shaft lengths, etc. a drawing is required.

**SPLINED SHAFT "I"**



**FLATTED SHAFT**

PA11/P11 - 2 = VHM

PA11/P11 - 7 = CDM




Fig. 9

**NEUTRAL MODULE "EN"**

Neutral or screen module is housed in a standard P11 module. It is used as a screen between two electrical modules.


The leads can be connected to ground.

**LOCATING PEGS** (Anti-rotation lugs)

The locating peg is provided by a plate mounted on the bushing and positioned by the module sides.

Four set positions are available, clock face orientation: 12, 3, 6, 9.

All P11 bushings have a double flat. When panel mounting holes have been punched accordingly, an anti-rotation lug is not necessary.



CODE	P11 - PA11					EFFECTIVE HIGH PEG
	VERSION	T-7	V-CC	Q	2-0	
B24	ø D mm	6.5	10.5	7.5	10	0.7
	ø d mm	2	2	2	2	
	L mm	6.2	6.2	6.2	6.2	
B30	ø d mm	2	2	2	2	0.7
	L mm	7.75	7.75	7.75	7.75	
B53	ø d mm	-	3.5	-	3.5	1.1
	L mm	-	13.5	-	13.5	

**TRIMMERS T11**

See data sheet document No. 51021

**MARKING**

**POTENTIOMETER MODULE**

VISHAY logo, nominal ohmic value (Ω, kΩ, MΩ), two stars identify PA11 version, tolerance in % - variation law, manufacturing date (four digits), "3" for the lead 3.

**SWITCH MODULE**

Version, manufacturing date (four digits), "c" for common lead.

**INDENT MODULE**

Version, manufacturing date (four digits).



# P11, PA11

Vishay Sfernice

Modular Potentiometers with Cermet (P11) or Conductive Plastic Elements (PA11)



## ORDERING INFORMATION

<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 50%;">P11 Cermet element</td> <td style="width: 50%;">PA11 Conductive plastic element</td> </tr> <tr> <td colspan="2" style="text-align: center;"><b>SERIES</b></td> </tr> </table>	P11 Cermet element	PA11 Conductive plastic element	<b>SERIES</b>		<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 50%;">Y Solder lugs - radial 4.70 mm (.200") pin spacing</td> <td style="width: 50%;">B24 Distance from shaft center of 6.2 mm (.244") for all models. Plate thickness of 0.4 mm (.015").</td> </tr> <tr> <td>X PCB pins - radial</td> <td>B30 Distance from shaft center of 7.75 mm (.305") for all models. Plate thickness of 0.4 mm (.015").</td> </tr> <tr> <td>Z PCB pins - radial with front support plate</td> <td>B53 Distance from shaft center of 13.5 mm (.531") for V, 2, CC and O models. Plate thickness of 0.8 mm (.031").</td> </tr> <tr> <td>A PCB pins - radial with front and back support plates</td> <td rowspan="2">Locating pegs can be placed at 12, 3, 6 or 9 o'clocks. Not available with panel and shaft sealing option P.</td> </tr> <tr> <td>W PCB pins - axial with 2 extra pins - 1 module only</td> </tr> <tr> <td>- 5.08 mm (.200") pin spacing for X, Z, W pins section 0.9 x 0.3 mm<sup>2</sup> (.035" x .012")</td> <td></td> </tr> <tr> <td>1 2.54 mm (.100") pin spacing for X, Z, W pins section 0.6 x 0.3 mm<sup>2</sup> (.024" x .012")</td> <td></td> </tr> <tr> <td>2 for X, Z, W pins section 0.6 x 0.3 mm<sup>2</sup> (.024" x .012")</td> <td></td> </tr> <tr> <td>- 5.08 mm (.200") space between modules</td> <td></td> </tr> <tr> <td>3 7.62 mm (.300") space between modules</td> <td></td> </tr> <tr> <td>4 10.16 mm (.400") space between modules</td> <td></td> </tr> <tr> <td colspan="2" style="text-align: center;"><b>TERMINAL STYLES</b></td> </tr> </table>	Y Solder lugs - radial 4.70 mm (.200") pin spacing	B24 Distance from shaft center of 6.2 mm (.244") for all models. Plate thickness of 0.4 mm (.015").	X PCB pins - radial	B30 Distance from shaft center of 7.75 mm (.305") for all models. Plate thickness of 0.4 mm (.015").	Z PCB pins - radial with front support plate	B53 Distance from shaft center of 13.5 mm (.531") for V, 2, CC and O models. Plate thickness of 0.8 mm (.031").	A PCB pins - radial with front and back support plates	Locating pegs can be placed at 12, 3, 6 or 9 o'clocks. Not available with panel and shaft sealing option P.	W PCB pins - axial with 2 extra pins - 1 module only	- 5.08 mm (.200") pin spacing for X, Z, W pins section 0.9 x 0.3 mm <sup>2</sup> (.035" x .012")		1 2.54 mm (.100") pin spacing for X, Z, W pins section 0.6 x 0.3 mm <sup>2</sup> (.024" x .012")		2 for X, Z, W pins section 0.6 x 0.3 mm <sup>2</sup> (.024" x .012")		- 5.08 mm (.200") space between modules		3 7.62 mm (.300") space between modules		4 10.16 mm (.400") space between modules		<b>TERMINAL STYLES</b>		<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td colspan="5" style="text-align: center;"><b>FROM MOUNTING FACE</b></td> </tr> <tr> <td>T</td> <td>K M R</td> <td>Dia. 3 3 3</td> <td>Length 9.5 12.5 22</td> <td>End Flat }</td> <td>End Shaft slotted</td> </tr> <tr> <td>Q</td> <td>E F G I</td> <td>4 4 4 6</td> <td>9.5 12.5 22 19</td> <td>} }</td> <td>slotted }</td> </tr> <tr> <td>V</td> <td>D N S</td> <td>6 6 6</td> <td>16 25 50</td> <td>} }</td> <td>slotted }</td> </tr> <tr> <td colspan="2">AP</td> <td colspan="4">Custom - specify or quote drawing.</td> </tr> <tr> <td>7</td> <td>CDM CK</td> <td>1/8" 1/8"</td> <td>5/8" 3/8"</td> <td>} }</td> <td>slotted</td> </tr> <tr> <td>7</td> <td>CM</td> <td>1/8"</td> <td>1/2"</td> <td rowspan="3">}</td> <td rowspan="3">slotted</td> </tr> <tr> <td>71</td> <td>CD</td> <td>1/8"</td> <td>5/8"</td> </tr> <tr> <td>72</td> <td>CH CR</td> <td>1/8" 1/8"</td> <td>3/4" 7/8"</td> </tr> <tr> <td>2</td> <td>VD VR VN VL VHM</td> <td>1/4" 1/4" 1/4" 1/4" 1/4"</td> <td>5/8" 7/8" 1" 1.1/2" 3/4"</td> <td rowspan="5">}</td> <td rowspan="5">slotted</td> </tr> <tr> <td>CC</td> <td>D</td> <td>6</td> <td>16</td> </tr> <tr> <td>CC-3</td> <td>U</td> <td>3</td> <td>28.5</td> </tr> <tr> <td>77</td> <td>CM</td> <td>1/8"</td> <td>1/2"</td> </tr> <tr> <td>77-3</td> <td>CR</td> <td>0.07"</td> <td>0.874"</td> </tr> <tr> <td>0</td> <td>VD</td> <td>1/4"</td> <td>5/8"</td> <td rowspan="2">}</td> <td rowspan="2">plain</td> </tr> <tr> <td>0-3</td> <td>VU</td> <td>1/8"</td> <td>9/8"</td> </tr> <tr> <td colspan="6" style="text-align: center;"><b>STANDARDS SHAFT LENGTHS</b></td> </tr> </table>	<b>FROM MOUNTING FACE</b>					T	K M R	Dia. 3 3 3	Length 9.5 12.5 22	End Flat }	End Shaft slotted	Q	E F G I	4 4 4 6	9.5 12.5 22 19	} }	slotted }	V	D N S	6 6 6	16 25 50	} }	slotted }	AP		Custom - specify or quote drawing.				7	CDM CK	1/8" 1/8"	5/8" 3/8"	} }	slotted	7	CM	1/8"	1/2"	}	slotted	71	CD	1/8"	5/8"	72	CH CR	1/8" 1/8"	3/4" 7/8"	2	VD VR VN VL VHM	1/4" 1/4" 1/4" 1/4" 1/4"	5/8" 7/8" 1" 1.1/2" 3/4"	}	slotted	CC	D	6	16	CC-3	U	3	28.5	77	CM	1/8"	1/2"	77-3	CR	0.07"	0.874"	0	VD	1/4"	5/8"	}	plain	0-3	VU	1/8"	9/8"	<b>STANDARDS SHAFT LENGTHS</b>						<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 15%;">SINGLE SHAFT</td> <td style="width: 15%;">BUSHING</td> <td style="width: 15%;">SHAFT DIA.</td> <td style="width: 15%;"></td> <td style="width: 15%;"></td> <td style="width: 15%;"></td> </tr> <tr> <td></td> <td>DIA.</td> <td>LENGTH</td> <td></td> <td></td> <td></td> </tr> <tr> <td>T</td> <td>6</td> <td>8</td> <td></td> <td>3</td> <td></td> </tr> <tr> <td>Q</td> <td>7</td> <td>8</td> <td></td> <td>4</td> <td></td> </tr> <tr> <td>V</td> <td>10</td> <td>9.5</td> <td></td> <td>6</td> <td></td> </tr> <tr> <td>2</td> <td>3/8"</td> <td>3/8"</td> <td></td> <td>1/4"</td> <td></td> </tr> <tr> <td>7</td> <td>1/4"</td> <td>1/4"</td> <td></td> <td>1/8"</td> <td></td> </tr> <tr> <td>71</td> <td>1/4"</td> <td>3/8"</td> <td></td> <td>1/8"</td> <td></td> </tr> <tr> <td>72</td> <td>1/4"</td> <td>1/2"</td> <td></td> <td>1/8"</td> <td></td> </tr> <tr> <td colspan="6" style="text-align: center;"><b>CONCENTRIC SHAFT</b></td> </tr> <tr> <td>CC</td> <td>10</td> <td>9.5</td> <td></td> <td>3 - 6</td> <td></td> </tr> <tr> <td>O</td> <td>3/8"</td> <td>3/8"</td> <td></td> <td>1/8" - 1/4"</td> <td></td> </tr> <tr> <td>77</td> <td>1/4"</td> <td>1/4"</td> <td></td> <td>0.07" - 1/8"</td> <td></td> </tr> <tr> <td colspan="6">*All panel sealing versions have a bushing of 8 mm dia, and 8 mm length</td> </tr> <tr> <td colspan="6" style="text-align: center;"><b>SHAFT AND BUSHING</b></td> </tr> </table>	SINGLE SHAFT	BUSHING	SHAFT DIA.					DIA.	LENGTH				T	6	8		3		Q	7	8		4		V	10	9.5		6		2	3/8"	3/8"		1/4"		7	1/4"	1/4"		1/8"		71	1/4"	3/8"		1/8"		72	1/4"	1/2"		1/8"		<b>CONCENTRIC SHAFT</b>						CC	10	9.5		3 - 6		O	3/8"	3/8"		1/8" - 1/4"		77	1/4"	1/4"		0.07" - 1/8"		*All panel sealing versions have a bushing of 8 mm dia, and 8 mm length						<b>SHAFT AND BUSHING</b>					
P11 Cermet element	PA11 Conductive plastic element																																																																																																																																																																																																														
<b>SERIES</b>																																																																																																																																																																																																															
Y Solder lugs - radial 4.70 mm (.200") pin spacing	B24 Distance from shaft center of 6.2 mm (.244") for all models. Plate thickness of 0.4 mm (.015").																																																																																																																																																																																																														
X PCB pins - radial	B30 Distance from shaft center of 7.75 mm (.305") for all models. Plate thickness of 0.4 mm (.015").																																																																																																																																																																																																														
Z PCB pins - radial with front support plate	B53 Distance from shaft center of 13.5 mm (.531") for V, 2, CC and O models. Plate thickness of 0.8 mm (.031").																																																																																																																																																																																																														
A PCB pins - radial with front and back support plates	Locating pegs can be placed at 12, 3, 6 or 9 o'clocks. Not available with panel and shaft sealing option P.																																																																																																																																																																																																														
W PCB pins - axial with 2 extra pins - 1 module only																																																																																																																																																																																																															
- 5.08 mm (.200") pin spacing for X, Z, W pins section 0.9 x 0.3 mm <sup>2</sup> (.035" x .012")																																																																																																																																																																																																															
1 2.54 mm (.100") pin spacing for X, Z, W pins section 0.6 x 0.3 mm <sup>2</sup> (.024" x .012")																																																																																																																																																																																																															
2 for X, Z, W pins section 0.6 x 0.3 mm <sup>2</sup> (.024" x .012")																																																																																																																																																																																																															
- 5.08 mm (.200") space between modules																																																																																																																																																																																																															
3 7.62 mm (.300") space between modules																																																																																																																																																																																																															
4 10.16 mm (.400") space between modules																																																																																																																																																																																																															
<b>TERMINAL STYLES</b>																																																																																																																																																																																																															
<b>FROM MOUNTING FACE</b>																																																																																																																																																																																																															
T	K M R	Dia. 3 3 3	Length 9.5 12.5 22	End Flat }	End Shaft slotted																																																																																																																																																																																																										
Q	E F G I	4 4 4 6	9.5 12.5 22 19	} }	slotted }																																																																																																																																																																																																										
V	D N S	6 6 6	16 25 50	} }	slotted }																																																																																																																																																																																																										
AP		Custom - specify or quote drawing.																																																																																																																																																																																																													
7	CDM CK	1/8" 1/8"	5/8" 3/8"	} }	slotted																																																																																																																																																																																																										
7	CM	1/8"	1/2"	}	slotted																																																																																																																																																																																																										
71	CD	1/8"	5/8"																																																																																																																																																																																																												
72	CH CR	1/8" 1/8"	3/4" 7/8"																																																																																																																																																																																																												
2	VD VR VN VL VHM	1/4" 1/4" 1/4" 1/4" 1/4"	5/8" 7/8" 1" 1.1/2" 3/4"	}	slotted																																																																																																																																																																																																										
CC	D	6	16																																																																																																																																																																																																												
CC-3	U	3	28.5																																																																																																																																																																																																												
77	CM	1/8"	1/2"																																																																																																																																																																																																												
77-3	CR	0.07"	0.874"																																																																																																																																																																																																												
0	VD	1/4"	5/8"	}	plain																																																																																																																																																																																																										
0-3	VU	1/8"	9/8"																																																																																																																																																																																																												
<b>STANDARDS SHAFT LENGTHS</b>																																																																																																																																																																																																															
SINGLE SHAFT	BUSHING	SHAFT DIA.																																																																																																																																																																																																													
	DIA.	LENGTH																																																																																																																																																																																																													
T	6	8		3																																																																																																																																																																																																											
Q	7	8		4																																																																																																																																																																																																											
V	10	9.5		6																																																																																																																																																																																																											
2	3/8"	3/8"		1/4"																																																																																																																																																																																																											
7	1/4"	1/4"		1/8"																																																																																																																																																																																																											
71	1/4"	3/8"		1/8"																																																																																																																																																																																																											
72	1/4"	1/2"		1/8"																																																																																																																																																																																																											
<b>CONCENTRIC SHAFT</b>																																																																																																																																																																																																															
CC	10	9.5		3 - 6																																																																																																																																																																																																											
O	3/8"	3/8"		1/8" - 1/4"																																																																																																																																																																																																											
77	1/4"	1/4"		0.07" - 1/8"																																																																																																																																																																																																											
*All panel sealing versions have a bushing of 8 mm dia, and 8 mm length																																																																																																																																																																																																															
<b>SHAFT AND BUSHING</b>																																																																																																																																																																																																															

Panel and shaft sealed

Concentric shafts

Locating peg

SHAFT AND BUSHING MODULE

OPTION INDENTS MODULE SWITCH MODULE 1st POTENTIOMETER MODULE 2nd POTENTIOMETER MODULE 3rd POT MODULE

PA11 7 X13 or B24 P CR CV1M RSD 100 k 20 % A J84 10 k 20 % A J + J84 100 k

**THE POSITION OF EACH MODULE IS FREE**

OPTION INDENTS MODULE SWITCH MODULE 1st POTENTIOMETER MODULE 2nd POTENTIOMETER MODULE 3rd POT MODULE

PA11 7 X13 or B24 P CR CV1M RSD 100 k 20 % A J84 10 k 20 % A J + J84 100 k


<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th colspan="2">OPTION INDENT MODULE</th> </tr> <tr> <td>CV1M</td> <td>1 indent at half travel</td> </tr> <tr> <td>CV1D</td> <td>1 indent CCW position</td> </tr> <tr> <td>CV1F</td> <td>1 indent CW position</td> </tr> <tr> <td>CV3</td> <td>3 indents inc. CW &amp; CCW</td> </tr> <tr> <td>-</td> <td>-</td> </tr> <tr> <td>-</td> <td>-</td> </tr> <tr> <td>-</td> <td>-</td> </tr> <tr> <td>CV11</td> <td>11 indents</td> </tr> <tr> <td>-</td> <td>-</td> </tr> <tr> <td>-</td> <td>-</td> </tr> <tr> <td>-</td> <td>-</td> </tr> <tr> <td>CV21</td> <td>21 indents etc.</td> </tr> <tr> <td colspan="2">Former CRN version (N-1 equal mechanical angles) available on request.</td> </tr> </table>	OPTION INDENT MODULE		CV1M	1 indent at half travel	CV1D	1 indent CCW position	CV1F	1 indent CW position	CV3	3 indents inc. CW & CCW	-	-	-	-	-	-	CV11	11 indents	-	-	-	-	-	-	CV21	21 indents etc.	Former CRN version (N-1 equal mechanical angles) available on request.		<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th colspan="2">OPTION SWITCH MODULE</th> </tr> <tr> <td>RSD</td> <td>Single pole open switch in CCW position - 2 pins</td> </tr> <tr> <td>RSF</td> <td>Single pole open switch in CW position - 2 pins</td> </tr> <tr> <td>RSID</td> <td>Single pole chargeover switch in CCW position - 3 pins</td> </tr> <tr> <td>RSIF</td> <td>Single pole chargeous switch in CW position - 3 pins</td> </tr> <tr> <td colspan="2">An assembly can comprise 1 or more switch modules. Pin out RS and RSI is the print out as other assembled modules.</td> </tr> </table>	OPTION SWITCH MODULE		RSD	Single pole open switch in CCW position - 2 pins	RSF	Single pole open switch in CW position - 2 pins	RSID	Single pole chargeover switch in CCW position - 3 pins	RSIF	Single pole chargeous switch in CW position - 3 pins	An assembly can comprise 1 or more switch modules. Pin out RS and RSI is the print out as other assembled modules.		<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th colspan="2">OHMIC VALUE</th> </tr> <tr> <td colspan="2">Quote clearly multipliers K - M</td> </tr> <tr> <td colspan="2">10 Ω to 10 MΩ</td> </tr> <tr> <td colspan="2">A linear law - cermet</td> </tr> <tr> <td colspan="2">100 Ω to 2.2 MΩ</td> </tr> <tr> <td colspan="2">L, F, S non linear laws - cermet</td> </tr> <tr> <td colspan="2">Conductive plastic</td> </tr> <tr> <td colspan="2">1 kΩ to 1MΩ A linear law</td> </tr> <tr> <td colspan="2">470 Ω to 500 kΩ non-linear laws</td> </tr> </table>	OHMIC VALUE		Quote clearly multipliers K - M		10 Ω to 10 MΩ		A linear law - cermet		100 Ω to 2.2 MΩ		L, F, S non linear laws - cermet		Conductive plastic		1 kΩ to 1MΩ A linear law		470 Ω to 500 kΩ non-linear laws		<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th colspan="2">VARIATION LAW</th> </tr> <tr> <td>A</td> <td>Linear</td> </tr> <tr> <td>L</td> <td>CW log 10 %</td> </tr> <tr> <td>F</td> <td>CW reverse log</td> </tr> <tr> <td>S</td> <td>Audio S shape symmetrical log</td> </tr> <tr> <td>W</td> <td>CW log 20 %</td> </tr> <tr> <td>RL</td> <td>CCW log</td> </tr> </table>	VARIATION LAW		A	Linear	L	CW log 10 %	F	CW reverse log	S	Audio S shape symmetrical log	W	CW log 20 %	RL	CCW log	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th colspan="2">TOLERANCE</th> </tr> <tr> <td>± 20 %</td> <td>Standard</td> </tr> <tr> <td>± 10 %</td> <td>Optional</td> </tr> <tr> <td>± 5 %</td> <td>Optional (cermet only)</td> </tr> </table>	TOLERANCE		± 20 %	Standard	± 10 %	Optional	± 5 %	Optional (cermet only)
OPTION INDENT MODULE																																																																																				
CV1M	1 indent at half travel																																																																																			
CV1D	1 indent CCW position																																																																																			
CV1F	1 indent CW position																																																																																			
CV3	3 indents inc. CW & CCW																																																																																			
-	-																																																																																			
-	-																																																																																			
-	-																																																																																			
CV11	11 indents																																																																																			
-	-																																																																																			
-	-																																																																																			
-	-																																																																																			
CV21	21 indents etc.																																																																																			
Former CRN version (N-1 equal mechanical angles) available on request.																																																																																				
OPTION SWITCH MODULE																																																																																				
RSD	Single pole open switch in CCW position - 2 pins																																																																																			
RSF	Single pole open switch in CW position - 2 pins																																																																																			
RSID	Single pole chargeover switch in CCW position - 3 pins																																																																																			
RSIF	Single pole chargeous switch in CW position - 3 pins																																																																																			
An assembly can comprise 1 or more switch modules. Pin out RS and RSI is the print out as other assembled modules.																																																																																				
OHMIC VALUE																																																																																				
Quote clearly multipliers K - M																																																																																				
10 Ω to 10 MΩ																																																																																				
A linear law - cermet																																																																																				
100 Ω to 2.2 MΩ																																																																																				
L, F, S non linear laws - cermet																																																																																				
Conductive plastic																																																																																				
1 kΩ to 1MΩ A linear law																																																																																				
470 Ω to 500 kΩ non-linear laws																																																																																				
VARIATION LAW																																																																																				
A	Linear																																																																																			
L	CW log 10 %																																																																																			
F	CW reverse log																																																																																			
S	Audio S shape symmetrical log																																																																																			
W	CW log 20 %																																																																																			
RL	CCW log																																																																																			
TOLERANCE																																																																																				
± 20 %	Standard																																																																																			
± 10 %	Optional																																																																																			
± 5 %	Optional (cermet only)																																																																																			

OPTIONS	
J	Center tap
J41	Panel sealed bushing 10 mm dia.
J44	Interlinearity ± 2 % (linear law)
J84	Accuracy of center point of CV1M to ± 2 % (except S law)
J123	Linearity ± 3 % (linear law)
J145	Linearity ± 2 % (linear law)
J152	Marking part number
EN	Empty module with screen
EV	Spacer module without pin
M	Motorized assembly
RSP	Push Push switch
RSPM	Momentary Push switch
Servo	Electrical travel 300°



**SAP PART NUMBERING GUIDELINES**



See the end of this data book for conversion tables





## Notice

Specifications of the products displayed herein are subject to change without notice. Vishay Intertechnology, Inc., or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document. Except as provided in Vishay's terms and conditions of sale for such products, Vishay assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of Vishay products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Vishay for any damages resulting from such improper use or sale.