



ZENER DIODES

T-11-11

500 mW ZENER DIODES/DO-35

OPERATING/STORAGE TEMPERATURE -65°C to +200°C

Device Type	Nominal Zener Voltage V _Z @ I _{ZT}	Test Current I _{ZT}	Maximum Zener Impedance		Typical Temperature Coefficient	Maximum Reverse Leakage Current		Maximum Regulator Current I _{ZM}
			Z _{ZT} @I _{ZT}	Z _{ZK} @I _{ZK} =0.25mA		I _R	@V _R	
	Volts	mA	Ohms	Ohms	%/°C	μA	Volts	mA
1N5221B	2.4	20	30	1200	-0.085	100	1.0	191
1N5222B	2.5	20	30	1250	-0.085	100	1.0	182
1N5223B	2.7	20	30	1300	-0.080	75	1.0	168
1N5224B	2.8	20	30	1400	-0.080	75	1.0	162
1N5225B	3.0	20	29	1600	-0.075	50	1.0	151
1N5226B	3.3	20	28	1600	-0.070	25	1.0	138
1N5227B	3.6	20	24	1700	-0.065	15	1.0	126
1N5228B	3.9	20	23	1900	-0.060	10	1.0	115
1N5229B	4.3	20	22	2000	±0.055	5.0	1.0	106
1N5230B	4.7	20	19	1900	±0.030	5.0	2.0	97
1N5231B	5.1	20	17	1600	±0.030	5.0	2.0	89
1N5232B	5.6	20	11	1600	+0.038	5.0	3.0	81
1N5233B	6.0	20	7.0	1600	+0.038	5.0	3.5	76
1N5234B	6.2	20	7.0	1000	+0.045	5.0	4.0	73
1N5235B	6.8	20	5.0	750	+0.050	3.0	5.0	67
1N5236B	7.5	20	6.0	500	+0.058	3.0	6.0	61
1N5237B	8.2	20	8.0	500	+0.062	3.0	6.5	55
1N5238B	8.7	20	8.0	600	+0.065	3.0	6.5	52
1N5239B	9.1	20	10	600	+0.068	3.0	7.0	50
1N5240B	10	20	17	600	+0.075	3.0	8.0	45
1N5241B	11	20	22	600	+0.076	2.0	8.4	41
1N5242B	12	20	30	600	+0.077	1.0	9.1	38
1N5243B	13	9.5	13	600	+0.079	0.5	9.9	35
1N5244B	14	9.0	15	600	+0.082	0.1	10	32
1N5245B	15	8.5	16	600	+0.082	0.1	11	30
1N5246B	16	7.8	17	600	+0.083	0.1	12	28
1N5247B	17	7.4	19	600	+0.084	0.1	13	27
1N5248B	18	7.0	21	600	+0.085	0.1	14	25
1N5249B	19	6.6	23	600	+0.085	0.1	14	24
1N5250B	20	6.2	25	600	+0.086	0.1	15	23
1N5251B	22	5.6	29	600	+0.087	0.1	17	21.2
1N5252B	24	5.2	33	600	+0.088	0.1	18	19.1
1N5253B	25	5.0	35	600	+0.089	0.1	19	18.2
1N5254B	27	4.6	41	600	+0.090	0.1	21	16.8
1N5255B	28	4.5	44	600	+0.091	0.1	21	16.2
1N5256B	30	4.2	49	600	+0.091	0.1	23	15.1
1N5257B	33	3.8	58	700	+0.092	0.1	25	13.8
1N5258B	36	3.4	70	700	+0.093	0.1	27	12.6
1N5259B	39	3.2	80	800	+0.094	0.1	30	11.5
1N5260B	43	3.0	93	900	+0.095	0.1	33	10.6
1N5261B	47	2.7	150	1000	+0.095	0.1	36	9.7
1N5262B	51	2.5	125	1100	+0.096	0.1	39	8.9
1N5263B	56	2.2	150	1300	+0.096	0.1	43	8.1

NOTE: Suffix "B" Indicates ±5% Tolerance.

1 WATT ZENER DIODES/DO-41

OPERATING/STORAGE TEMPERATURE RANGE -55°C to +175°C

TYPE	NORMAL ZENER VOLTAGE @ I _{ZT}	DYNAMIC IMPEDANCE				MAXIMUM REVERSE CURRENT		MAX. ZENER CURRENT mA
		I _{ZT} (mA)	Z _{ZT} (OHMS)	I _{ZK} (mA)	Z _{ZK} (OHMS)	V _R (V)	I _R (μA)	
Z100B	100	5.0	600	.25	5000	75	0.5	7
Z120B	120	5.0	850	.25	5000	90	0.5	6
Z150B	150	5.0	1150	.25	5000	115	0.5	5
Z180B	180	5.0	2200	.25	5000	140	0.5	4

NOTE: Suffix "B" Indicates ±5% Tolerance.