



Types	I _O (A)	V _{RRM} (V)	I _{FSM} 10 ms (A)	V _F / I _F max (V) / (A)	I _R @ V _{RRM} max (mA)	T _{amb} (°C)	Case
-------	-----------------------	-------------------------	----------------------------------	---	--	--------------------------	------


1 A / T_{amb} = 70°C T_j = 200°C

1N 5614 1N 5616 1N 5618 1N 5620 1N 5622	1	200 400 600 800 1000	50	1,2	1	0,025	100	 BV 10 glass - verre (CB-316)
---	---	----------------------------------	----	-----	---	-------	-----	---

1 A / T_{amb} = 75°C T_j = 150°C

PY 126 PY 127	1	650 1250	100	1,1	1	0,005	25	 F 126 plastic - plastique (CB-210)
------------------	---	-------------	-----	-----	---	-------	----	---

1 A / T_{amb} = 100°C T_j = 175°C

1N 3189 1N 3190 1N 3191 1N 2616 1N 2617	1	200 400 600 800 1000	30	1	1	0,15 0,15 0,15 0,50 0,50	150	 DO 13 metal (CB-37)
---	---	----------------------------------	----	---	---	--------------------------------------	-----	--


1,25 A / T_{amb} = 25°C T_j = 150°C

F 11 F 21 F 41 F 61 F 81 F 101 F 121	1,25	100 200 400 600 800 1000 1200	30	1,2	1,25	1	150
--	------	---	----	-----	------	---	-----

2 A / T_{amb} = 25°C T_j = 175°C

F 12 F 22 F 42 F 62 F 82 F 102	2	100 200 400 600 800 1000	70	1,2	2	1	150
---	---	---	----	-----	---	---	-----

3 A / T_{amb} = 50°C T_j = 150°C

BY 251 BY 252 BY 253 BY 254 BY 254 S BY 255	3	200 400 600 800 1000 1300	100	1,1	3	0,005	25	 DO 27 A plastic - plastique (CB-197)
--	---	--	-----	-----	---	-------	----	---

N

N : New product
Nouveau produit