



Micro Commercial Components



Micro Commercial Components
20736 Marilla Street Chatsworth
CA 91311
Phone: (818) 701-4933
Fax: (818) 701-4939

3KP5.0(C)(A) THRU 3KP220(C)(A)


Features

- 3000 Watts Peak Power
- Low Inductance
- Unidirectional and Bidirectional unit
- Voltage Range: 5.0 to 220 Volts.
- UL Recognized File # E331408
- Lead Free Finish/RoHS Compliant(Note 1) ("P" Suffix designates RoHS Compliant. See ordering information)

Mechanical Data

- Epoxy meets UL 94 V-0 flammability rating
- Moisture Sensitivity Level 1
- Marking : Cathode band(For Uni-directional) and type number
- Suffix "C" of part number denotes Bi-directional unit.
- Halogen free available upon request by adding suffix "-HF"

3000Watts Transient Voltage Suppressor 5.0 to 220 Volts



Electrical Characteristics @ 25°C Unless Otherwise Specified

| RATING | SYMBOL | VALUE | UNITS |
|---------------------------------------------------------------------------------------------------|----------------|--------------|------------------|
| Peak Pulse Power Dissipation on 10/1000us waveform (Note 2, FIG.1) | P_{PPM} | Minimum 3000 | Watts |
| Steady State Power Dissipation at $T_L = 75^\circ\text{C}$, Lead lengths .375", (9.5mm) (Note 3) | $P_{M(AV)}$ | 8 | Watts |
| Operating junction and Storage Temperature Range | P_J, T_{STG} | -55 to +175 | $^\circ\text{C}$ |

Notes :

- 1.High Temperature Solder Exemption Applied, see EU Directive Annex 7.
- 2.Non-repetitive current pulse , per Fig. 3 and derated above $T_A = 25$ per Fig. 2 .
- 3.Mounted on Copper Pad area of 1.6jÅ1.6" (40jÅ40mm) per Fig. 5.

3KP Series

| 3KP PART NUMBER | | REVERSE STAND- OFF VOLTAGE $V_{RWM}(V)$ | BREAKDOWN VOLTAGE $V_{BR}(V)$ MIN.@ I_T | BREAKDOWN VOLTAGE $V_{BR}(V)$ MAX.@ I_T | TEST CURRENT I_T (mA) | MAXIMUM CLAMPING VOLTAGE @ $I_{pp} V_c(V)$ | PEAK PULSE CURRENT I_{pp} (A) | REVERSE LEAKAGE @ $V_{RWM} I_R(\mu$ A) |
|--------------------|----------|-----------------------------------------------------|----------------------------------------------------|----------------------------------------------------|-------------------------------|-----------------------------------------------------|------------------------------------------|-------------------------------------------------|
| UNI-POLAR | BI-POLAR | | | | | | | |
| 3KP5.0A | 3KP5.0CA | 5.0 | 6.40 | 7.00 | 50 | 9.2 | 326.1 | 5000 |
| 3KP6.0A | 3KP6.0CA | 6.0 | 6.67 | 7.37 | 50 | 10.3 | 291.3 | 5000 |
| 3KP6.5A | 3KP6.5CA | 6.5 | 7.22 | 7.98 | 50 | 11.2 | 267.9 | 2000 |
| 3KP7.0A | 3KP7.0CA | 7.0 | 7.78 | 8.60 | 50 | 12.0 | 250.0 | 1000 |
| 3KP7.5A | 3KP7.5CA | 7.5 | 8.33 | 9.21 | 5 | 12.9 | 232.6 | 250 |
| 3KP8.0A | 3KP8.0CA | 8.0 | 8.89 | 9.83 | 5 | 13.6 | 220.6 | 150 |
| 3KP8.5A | 3KP8.5CA | 8.5 | 9.44 | 10.40 | 5 | 14.4 | 208.3 | 50 |
| 3KP9.0A | 3KP9.0CA | 9.0 | 10.00 | 11.10 | 5 | 15.4 | 194.8 | 20 |
| 3KP10A | 3KP10CA | 10.0 | 11.10 | 12.30 | 5 | 17.0 | 176.5 | 15 |
| 3KP11A | 3KP11CA | 11.0 | 12.20 | 13.50 | 5 | 18.2 | 164.8 | 10 |
| 3KP12A | 3KP12CA | 12.0 | 13.30 | 14.70 | 5 | 19.9 | 150.8 | 10 |
| 3KP13A | 3KP13CA | 13.0 | 14.40 | 15.90 | 5 | 21.5 | 139.5 | 10 |
| 3KP14A | 3KP14CA | 14.0 | 15.60 | 17.20 | 5 | 23.2 | 129.3 | 10 |
| 3KP15A | 3KP15CA | 15.0 | 16.70 | 18.50 | 5 | 24.4 | 123.0 | 10 |
| 3KP16A | 3KP16CA | 16.0 | 17.80 | 19.70 | 5 | 26.0 | 115.4 | 10 |
| 3KP17A | 3KP17CA | 17.0 | 18.90 | 20.90 | 5 | 27.6 | 108.7 | 10 |
| 3KP18A | 3KP18CA | 18.0 | 20.00 | 22.10 | 5 | 29.2 | 102.7 | 10 |
| 3KP20A | 3KP20CA | 20.0 | 22.20 | 24.50 | 5 | 32.4 | 92.6 | 10 |
| 3KP22A | 3KP22CA | 22.0 | 24.40 | 26.90 | 5 | 35.5 | 84.5 | 10 |
| 3KP24A | 3KP24CA | 24.0 | 26.70 | 29.50 | 5 | 38.9 | 77.1 | 10 |
| 3KP26A | 3KP26CA | 26.0 | 28.90 | 31.90 | 5 | 42.1 | 71.3 | 10 |
| 3KP28A | 3KP28CA | 28.0 | 31.10 | 34.40 | 5 | 45.4 | 66.1 | 10 |
| 3KP30A | 3KP30CA | 30.0 | 33.30 | 36.80 | 5 | 48.4 | 62.0 | 10 |
| 3KP33A | 3KP33CA | 33.0 | 36.70 | 40.60 | 5 | 53.3 | 56.3 | 10 |
| 3KP36A | 3KP36CA | 36.0 | 40.00 | 44.20 | 5 | 58.1 | 51.6 | 10 |
| 3KP40A | 3KP40CA | 40.0 | 44.40 | 49.10 | 5 | 64.5 | 46.5 | 10 |
| 3KP43A | 3KP43CA | 43.0 | 47.80 | 52.80 | 5 | 69.4 | 43.2 | 10 |
| 3KP45A | 3KP45CA | 45.0 | 50.00 | 55.30 | 5 | 72.7 | 41.3 | 10 |
| 3KP48A | 3KP48CA | 48.0 | 53.30 | 58.90 | 5 | 77.4 | 38.8 | 10 |
| 3KP51A | 3KP51CA | 51.0 | 56.70 | 62.70 | 5 | 82.4 | 36.4 | 10 |
| 3KP54A | 3KP54CA | 54.0 | 60.00 | 66.30 | 5 | 87.1 | 34.4 | 10 |
| 3KP58A | 3KP58CA | 58.0 | 64.40 | 71.20 | 5 | 93.6 | 32.1 | 10 |
| 3KP60A | 3KP60CA | 60.0 | 66.70 | 73.70 | 5 | 96.8 | 31.0 | 10 |
| 3KP64A | 3KP64CA | 64.0 | 71.10 | 78.60 | 5 | 103.0 | 29.1 | 10 |
| 3KP70A | 3KP70CA | 70.0 | 77.80 | 86.00 | 5 | 113.0 | 26.5 | 10 |
| 3KP75A | 3KP75CA | 75.0 | 83.30 | 92.10 | 5 | 121.0 | 24.8 | 10 |
| 3KP78A | 3KP78CA | 78.0 | 86.70 | 95.80 | 5 | 126.0 | 23.8 | 10 |
| 3KP85A | 3KP85CA | 85.0 | 94.40 | 104.00 | 5 | 137.0 | 21.9 | 10 |
| 3KP90A | 3KP90CA | 90.0 | 100.00 | 111.00 | 5 | 146.0 | 20.5 | 10 |
| 3KP100A | 3KP100CA | 100.0 | 111.00 | 123.00 | 5 | 162.0 | 18.5 | 10 |
| 3KP110A | 3KP110CA | 110.0 | 122.00 | 135.00 | 5 | 177.0 | 16.9 | 10 |
| 3KP120A | 3KP120CA | 120.0 | 133.00 | 147.00 | 5 | 193.0 | 15.5 | 10 |
| 3KP130A | 3KP130CA | 130.0 | 144.00 | 159.00 | 5 | 209.0 | 14.4 | 10 |
| 3KP150A | 3KP150CA | 150.0 | 167.00 | 185.00 | 5 | 243.0 | 12.3 | 10 |
| 3KP160A | 3KP160CA | 160.0 | 178.00 | 197.00 | 5 | 259.0 | 11.6 | 10 |
| 3KP170A | 3KP170CA | 170.0 | 189.00 | 209.00 | 5 | 275.0 | 10.9 | 10 |
| 3KP180A | 3KP180CA | 180.0 | 200.00 | 221.00 | 5 | 289.0 | 10.4 | 10 |
| 3KP190A | 3KP190CA | 190.0 | 211.00 | 233.00 | 5 | 310.0 | 9.7 | 10 |
| 3KP200A | 3KP200CA | 200.0 | 222.00 | 246.00 | 5 | 329.2 | 9.1 | 10 |
| 3KP210A | 3KP210CA | 210.0 | 233.00 | 258.00 | 5 | 349.5 | 8.6 | 10 |
| 3KP220A | 3KP220CA | 220.0 | 244.00 | 270.00 | 5 | 371.1 | 8.1 | 10 |

For bidirectional type having V_{rwm} of 10 volts and less, the IR limit is double.

For parts without A, the V_{BR} is $\pm 10\%$

3KP Series

RATINGS AND CHARACTERISTIC CURVES (TA=25°C unless otherwise noted)



Micro Commercial Components

Fig. 1 - Peak Pulse Power Rating Curve




Fig.2 - Pulse Derating Curve




Fig.3 - Pulse Waveform




Fig. 4 - Typical Junction Capacitance




Fig. 5 - Steady State Power Derating Curve





Fig.6 - Maximum Non-repetitive Forward Surge current





Micro Commercial Components

Ordering Information :

| Device | Packing |
|----------------|-------------------------------|
| Part Number-TP | Tape&Reel: 500pcs/Reel |
| Part Number-AP | Ammo Packing: 450pcs/Ammo Box |
| Part Number-BP | Bulk: 4.8Kpcs/Carton |

Note : Adding "-HF" suffix for halogen free, eg. Part Number-TP-HF

IMPORTANT NOTICE

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications , enhancements , improvements , or other changes . **Micro Commercial Components Corp .** does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights ,nor the rights of others . The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp .** and all the companies whose products are represented on our website, harmless against all damages.

LIFE SUPPORT

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

CUSTOMER AWARENESS

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources.** MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

www.mccsemi.com