

General Transistor Corporation  
 216 WEST FLORENCE AVENUE  
 INGLEWOOD, CALIFORNIA 90301  
 (213) 673-8422 • Telex 65-3474 • FAX (213) 672-2905

**CASE TO-3, TO-39**  
 $I_C(\text{MAX}) = 3-50A$   
 $V_{CEO(\text{SUS})} = 40-100V$

T-33-01

**PNP Power Transistors**

Type No.	NPN complement	V <sub>CEO</sub> (max) (V)	I <sub>C</sub> (max) (A)	h <sub>FE</sub> @I <sub>C</sub> /V <sub>CE</sub> (min-max @ A/V)	V <sub>CE(SAT)</sub> @ I <sub>C</sub> /I <sub>B</sub> (V @ A/A)	V <sub>BE</sub> @ I <sub>C</sub> /V <sub>CE</sub> (V @ A/V)	V <sub>BE(SAT)</sub> @ I <sub>C</sub> /I <sub>B</sub> (V @ A/A)	I <sub>CEV</sub> @ V <sub>CE</sub> (mA @ V)	P <sub>D</sub> @ TC = 25°C (Watts)	I <sub>sb</sub> @V <sub>CE</sub> t = 1 sec (A @ V)	f <sub>r</sub> (MHz)	t <sub>on</sub> @ I <sub>C</sub> /I <sub>B</sub> (μs @ A/A)	t <sub>OFF</sub> @ I <sub>C</sub> /I <sub>B</sub> (μs @ A/A)
2N3789	2N3713	60	10	25-90 @ 1/2	1 @ 4/4		2 @ 4/4	1 @ 60	150	5 @ 30	4	.7 @ 4/4	1.8 @ 4/4
2N3790	2N3714	80	10	25-90 @ 1/2	1 @ 4/4		2 @ 4/4	1 @ 80	150	5 @ 30	4	.7 @ 4/4	1.8 @ 4/4
2N3791	2N3715	60	10	50-150 @ 1/2	1 @ 5/5		1.5 @ 5/5	1 @ 60	150	5 @ 30	4	.7 @ 4/4	1.8 @ 4/4
2N3792	2N3716	80	10	50-150 @ 1/2	1 @ 5/5		1.5 @ 5/5	1 @ 80	150	5 @ 30	4	.7 @ 4/4	1.8 @ 4/4
2N4398	2N5301	40	30	15-60 @ 15/2	2 @ 20/2	1.7 @ 15/2		5 @ 40	200	6.7 @ 30	4	.4 @ 10/1	2.1 @ 10/1
2N4399	2N5302	60	30	15-60 @ 15/2	2 @ 20/2	1.7 @ 15/2		5 @ 60	200	6.7 @ 30	4	.4 @ 10/1	2.1 @ 10/1
2N4901	2N5067	40	5	20-80 @ 1/2	1.5 @ 5/1	1.2 @ 1/2		.1 @ 40	87.5	5 @ 17.5	4	.7 @ 1.5/15	1.8 @ 1.5/15
2N4902	2N5068	60	5	20-80 @ 1/2	1.5 @ 5/1	1.2 @ 1/2		.1 @ 60	87.5	5 @ 17.5	4	.7 @ 1.5/15	1.8 @ 1.5/15
2N4903	2N5069	80	5	20-80 @ 1/2	1.5 @ 5/1	1.2 @ 1/2		.1 @ 80	87.5	5 @ 17.5	4	.7 @ 1.5/15	1.8 @ 1.5/15
2N4904	2N4913	40	5	25-100 @ 2.5/2	1.5 @ 5/1	1.4 @ 2.5/2		.1 @ 40	87.5	5 @ 17.5	4	.7 @ 4/4	1.8 @ 4/4
2N4905	2N4914	60	5	25-100 @ 2.5/2	1.5 @ 5/1	1.4 @ 2.5/2		.1 @ 60	87.5	5 @ 17.5	4	.7 @ 4/4	1.8 @ 4/4
2N4906	2N4915	80	5	25-100 @ 2.5/2	1.5 @ 5/1	1.4 @ 2.5/2		.1 @ 80	87.5	5 @ 17.5	4	.7 @ 4/4	1.8 @ 4/4
2N5683	2N5685	60	50	15-60 @ 25/2	1 @ 25/2.5	2 @ 25/2		2 @ 60	300	10 @ 30	2	.7 @ 25/2.5	1.8 @ 25/2.5
2N5684	2N5686	80	50	15-60 @ 25/2	1 @ 25/2.5	2 @ 25/2		2 @ 80	300	10 @ 30	2	.7 @ 25/2.5	1.8 @ 25/2.5
2N5745	2N5303	80	20	15-60 @ 10/2	2 @ 20/4	1.5 @ 10/2		5 @ 80	200	6.7 @ 30	2	1 @ 10/1	3 @ 10/1
2N5867	2N5869	60	5	20-100 @ 1.5/4	1 @ 2/2		1.6 @ 2/2	.1 @ 60	87.5	3.5 @ 25	4	.7 @ 1.5/15	1.8 @ 1.5/15
2N5868	2N5870	80	5	20-100 @ 2.5/4	1 @ 2/2		1.6 @ 2/2	.1 @ 80	87.5	3.5 @ 25	4	.7 @ 1.5/15	1.8 @ 1.5/15
2N5871	2N5873	60	7	20-100 @ 2.5/4	1 @ 4/4		1.6 @ 4/4	25 @ 60	100	3.3 @ 30	4	.7 @ 2.5/25	1.8 @ 2.5/25
2N5872	2N5874	80	7	20-100 @ 2.5/4	1 @ 4/4		1.6 @ 4/4	25 @ 80	100	3 @ 33	4	.7 @ 2.5/25	1.8 @ 2.5/25
2N5875	2N5877	60	10	20-100 @ 4/4	1 @ 5/5		1.6 @ 5/5	5 @ 60	150	5 @ 30	4	.7 @ 4/4	1.8 @ 4/4
2N5876	2N5878	80	10	20-100 @ 4/4	1 @ 5/5		1.6 @ 5/5	5 @ 80	150	4.5 @ 33	4	.7 @ 4/4	1.8 @ 4/4
2N5879	2N5881	60	15	20-100 @ 6/4	1 @ 7/7		1.6 @ 7/7	5 @ 60	160	5.33 @ 30	4	.7 @ 6/6	1.8 @ 6/6
2N5880	2N5882	80	15	20-100 @ 6/4	1 @ 7/7		1.6 @ 7/7	5 @ 80	160	4 @ 40	4	.7 @ 6/6	1.8 @ 6/6
2N5883	2N5885	60	25	20-100 @ 10/4	1 @ 15/1.5		1.8 @ 15/1.5	1 @ 60	200	6 @ 33	4	.7 @ 10/1	1.8 @ 10/1
2N5884	2N5888	80	25	20-100 @ 10/4	1 @ 15/1.5		1.8 @ 15/1.5	1 @ 80	200	5 @ 40	4	.7 @ 10/1	1.8 @ 10/1
2N6246		60	15	20-100 @ 7/4	1.3 @ 7/7	2 @ 7/4		.2 @ 65	125	7.1 @ 17.5	6	.7 @ 6/6	1.8 @ 6/6
2N6247		80	15	20-100 @ 6/4	1.3 @ 6/6	1.8 @ 6/4		.2 @ 85	125	7.1 @ 17.5	6	.7 @ 6/6	1.8 @ 6/6
2N6329	2N6326	60	30	6-30 @ 30/4	1.5 @ 15/2	2 @ 15/4		.5 @ 60	200	10 @ 20	3	.4 @ 10/1	1.8 @ 10/1
2N6330	2N6327	80	30	6-30 @ 30/4	1.5 @ 15/2	2 @ 15/4		.5 @ 80	200	10 @ 20	3	.4 @ 10/1	1.8 @ 10/1
2N6331	2N6328	100	30	6-30 @ 30/4	1.5 @ 15/2	2 @ 15/4		.5 @ 100	200	10 @ 20	3	.4 @ 10/1	1.8 @ 10/1
2N6436		80	25	20-80 @ 10					200		40		
2N6437		100	25	20-80 @ 10					200		40		
2N6438		120	25	20-80 @ 10					200		40		
2N6377		80	50	30-120 @ 20					250		30		
2N6378		100	50	30-120 @ 20					250		30		
2N6379		120	50	30-120 @ 20					250		30		
MJ6502		250	8	15 @ 2					125				
MJ6503		400	8	15 @ 2					125				

NOTES: b) I<sub>CBO</sub> @ V<sub>CB</sub> (mA @ V) g) I<sub>CES</sub> @ V<sub>CE</sub> (mA @ V) h) V<sub>CER</sub> (V) i) (typical)

General Transistor Corporation  
 216 WEST FLORENCE AVENUE  
 INGLEWOOD, CALIFORNIA 90301  
 (213) 673-8422 • Telex 65-3474 • FAX (213) 672-2905

**CASE TO-5/TO-39**  
 $I_C(MAX) = 0.05-10A$   
 $V_{CEO(SUS)} = 40-800V$

**NPN Power Transistors**

Type No.	PNP complement	V <sub>CEO</sub> (max) (V)	I <sub>C</sub> (max) (A)	hFE@I <sub>C</sub> /V <sub>CE</sub> (min-max @ A/V)	V <sub>CE(SAT)</sub> @ I <sub>C</sub> /I <sub>B</sub> (V @ A/A)	V <sub>BE</sub> @ I <sub>C</sub> /V <sub>CE</sub> (V @ A/V)	V <sub>BE(SAT)</sub> @ I <sub>C</sub> /I <sub>B</sub> (V @ A/A)	I <sub>CEV</sub> @ V <sub>CE</sub> (mA @ V)	P <sub>D</sub> @ T <sub>C</sub> = 25°C (Watts)	I <sub>sb</sub> @V <sub>CE</sub> t = 1 sec (A @ V)	f <sub>r</sub> (MHz)	t <sub>on</sub> @ I <sub>C</sub> /I <sub>B</sub> (μs @ A/A)	t <sub>OFF</sub> @ I <sub>C</sub> /I <sub>B</sub> (μs @ A/A)
2N1479		40	1.5	20-60 @ .2/4	1.4 @ 2/0.2	3 @ 2/4		.25 @ 60	5	150	1.5	5 @ 1/1	15 @ 1/1
2N1480		55	1.5	20-60 @ .2/4	1.4 @ 2/0.2	3 @ 2/4		.25 @ 100	5	150	1.5	5 @ 1/1	15 @ 1/1
2N1481		40	1.5	35-100 @ .2/4	1.4 @ 2/0.1	3 @ 2/4		.25 @ 60	5	150	1.5	5 @ 1/1	15 @ 1/1
2N1482		55	1.5	35-100 @ .2/4	1.4 @ 2/0.1	3 @ 2/4		.25 @ 100	5	150	1.5	5 @ 1/1	15 @ 1/1
2N1700		40	1.0	20-80 @ .1/4	1 @ 1/0.1	2 @ .1/4		.5 @ 60	5	150*	1.2	5 @ 1/1	15 @ 1/1
2N3418		60	3.0	20-60 @ 1/2	.25 @ 1/1	1.2 @ 1/2		.0005 @ 80	7	150	10	.3 @ 1/1	1.2 @ 1/1
2N3419		80	3.0	20-60 @ 1/2	.25 @ 1/1	1.2 @ 1/2		.0005 @ 120	7	150	40	.3 @ 1/1	1.2 @ 1/1
2N3420		60	3.0	40-120 @ 1/2	.25 @ 1/1	1.2 @ 1/2		.0005 @ 80	7	150	40	.3 @ 1/1	1.2 @ 1/1
2N3431		80	3.0	40-120 @ 1/2	.25 @ 1/1	1.2 @ 1/2		.0005 @ 120	7	150	40	.3 @ 1/1	1.2 @ 1/1
2N3439	2N5416	350	1.0	40-60 @ .02/10	.5 @ .05/0.04		1.3 @ .05/0.04	.5 @ 450	10	10	15		
2N3440	2N5415	250	1.0	40-60 @ .02/10	.5 @ .05/0.04		1.3 @ .05/0.04	.5 @ 300	10	10	15		
2N3742	2N3743	300	.05	20-200 @ .03/10	1 @ .01/0.01		1.2 @ .03/0.03	.0002 @ 200	5	6	15'		
2N4150		70	5.0	40-120 @ 5/5	.6 @ 5/5		1.5 @ 5/5	.01 @ 100	8.75	150*	15	.2 @ 5/5	2.2 @ 5/5
2N4237	2N4234	40	3.0	30 @ .25/1	.6 @ 1/1				6				
2N4238	2N4235	60	3.0	30 @ .25/1	.6 @ 1/1				6				
2N4239	2N4236	80	3.0	30 @ .25/1	.6 @ 1/1				6				
2N4271		140	1.0	20-140 @ .2/10	.8 @ 2/0.2	1 @ .2/10		.02 @ 175	10	25	20		
2N4272		140	2.5	20-140 @ 1/10	.6 @ 5/0.5	1.1 @ 1/10		.1 @ 175	10	75	10		
2N4863		120	2.0	50-150 @ .5/5	.2 @ 5/0.5		1.2 @ .5/5	.01 @ 140	7	25'	50		
2N4877		60	4.0	20-100 @ 4/2	1 @ 4/4		1.8 @ 4/4	.1 @ 170	10	150*	30	.1 @ 4/4	2 @ 4/4
2N4895		60	5.0	40 @ 2/2	1.0 @ 5/5				7				
2N4896		60	5.0	100 @ 2/2	1.0 @ 5/5				7				
2N4897		80	5.0	40 @ 2/2	1.0 @ 5/5				7				
2N4926	2N4930	200	.05	20-200 @ .03/10	1 @ .01/0.01		1.5 @ .05/0.03	.1 @ 200	5	6	15'		
2N4927	2N4931	250	.05	20-200 @ .03/10	1 @ .01/0.01		1.5 @ .05/0.03	.1 @ 250	5	6	15'		
2N5010		500*	.5	30-180 @ .025/10	1.4 @ .025/0.005		1 @ .025/0.005	.006 @ 400	4	25	15'		
2N5011		600*	.5	30-180 @ .025/10	1.5 @ .025/0.005		1 @ .025/0.005	.006 @ 500	4	25	15'		
2N5012		700*	.5	30-180 @ .025/10	1.6 @ .025/0.005		1 @ .025/0.005	.006 @ 580	4	25	15'		
2N5013		800*	.5	30-180 @ .02/10	1.6 @ .02/0.005		1 @ .02/0.005	.012 @ 650	4	25	15'		
2N5058		300	.15	35-150 @ .03/25	1 @ .03/0.03		.85 @ .03/0.03	.1 @ 300	5	10	15'		
2N5059		250	.15	35-150 @ .03/25	1 @ .03/0.03		.85 @ .03/0.03	.1 @ 250	5	10	15'		
2N5092	2N5093	350	1.0	15-250 @ .1/10	.5 @ .025/0.025	1 @ .025/5		.1 @ 400	4	15	15'		
2N5095	2N5094	400	1.0	15-250 @ .1/10	.5 @ .025/0.025	1 @ .025/5		.1 @ 500	4	15	15'		
2N5097	2N5096	450	1.0	15-250 @ .1/10	.5 @ .025/0.025	1 @ .025/5		.1 @ 600	4	15	15'		
2N5098		500	1.0	15-250 @ .1/10	.5 @ .025/0.025	1 @ .025/5		.1 @ 700	4	15	15'		
2N5099		550	1.0	15-250 @ .1/10	.5 @ .025/0.025	1 @ .025/5		.1 @ 800	4	15	15'		
2N5148	2N5147	80	2.0	30-90 @ 1/5	.85 @ 2/2	1.5 @ 2/5		1 @ 100	7	70	50	.3 @ 1/1	1.2 @ 1/1
2N5150	2N5149	80	2.0	70-200 @ 2.5/5	.85 @ 2/2	1.5 @ 2/5		1 @ 100	7	70	50'	.3 @ 1/1	1.2 @ 1/1
2N5152	2N5151	80	2.0	30-90 @ 2.5/25	.75 @ 2.5/25	1.45 @ 2.5/5		1 @ 100	11.7	250	40'	.3 @ 5/5	1.5 @ 5/5
2N5154	2N5153	80	2.0	70-200 @ 2.5/5	.75 @ 2.5/25	1.45 @ 2.5/5		1 @ 100	11.7	250	40'	.3 @ 5/5	1.5 @ 5/5
2N5237		120	5.0	40-120 @ 5/5	.6 @ 5/5		1.5 @ 5/5	.01 @ 150	8.75	150*	25	.5 @ 5/5	2 @ 5/5
2N5238		170	5.0	40-120 @ 5/5	.6 @ 5/5		1.5 @ 5/5	.01 @ 200	8.75	150*	25	.5 @ 5/5	2 @ 5/5
2N5334		60	3.0	30-150 @ 1/2	.7 @ 2/2		1.5 @ 2/2	.001 @ 60	6	75	40	.3 @ 1/1	1.2 @ 1/1
2N5335		80	3.0	30-150 @ 1/2	.7 @ 2/2		1.5 @ 2/2	.001 @ 80	6	75	50t	.3 @ 1/1	1.2 @ 1/1
2N5336		80	5.0	30-120 @ 2/2	1.2 @ 5/5		1.2 @ 2/2	.01 @ 75	6	250	30	.3 @ 5/5	1.5 @ 5/5
2N5337		80	5.0	60-240 @ 2/2	1.2 @ 5/5		1.2 @ 2/2	.01 @ 75	6	250	30	.3 @ 5/5	1.5 @ 5/5
2N5338		100	5.0	30-120 @ 2/2	1.2 @ 5/5		1.2 @ 2/2	.01 @ 90	6	250	30	.3 @ 5/5	1.5 @ 5/5
2N5339		100	5.0	60-240 @ 2/2	1.2 @ 5/5		1.2 @ 2/2	.01 @ 90	6	250	30	.3 @ 5/5	1.5 @ 5/5
2N5541		130	5.0	30-90 @ 5/5	.6 @ 5/5		1.5 @ 5/5	.01 @ 175	8.75	150*	20	.5 @ 5/5	2 @ 5/5
2N5681	2N5679	100	1.0	40 @ .25/2	1.0 @ .5/0.5				10				
2N5682	2N5680	120	1.0	40 @ .25/2	1.0 @ .5/0.5			1 @ 100	10				
2N5729		80	5.0	30-300 @ 2/2	1.5 @ 5/5		1.5 @ 5/5		11.7	150	30	.2 @ 2/2	3.5 @ 2/2
2N5784		65	3.5	20-100 @ 1/2	2 @ 3.2/8	1.5 @ 1/2		.01 @ 75	10	150*	1	5 @ 1/1	15 @ 1/1
2N5785		50	3.5	20-100 @ 1.2/2	2 @ 3.2/8	1.5 @ 1.2/2		.01 @ 60	10	150*	1	5 @ 1/1	15 @ 1/1
2N5786		40	3.5	20-100 @ 1.6/2	2 @ 3.2/8	1.5 @ 1.6/2		.01 @ 45	10	150*	1	5 @ 1/1	15 @ 1/1

NOTES: b) I<sub>CBO</sub> @ V<sub>CB</sub> (MA @ V) g) I<sub>CES</sub> @ V<sub>CE</sub> (mA @ V) h) V<sub>GER</sub> (V) t) (typical)

**General Transistor Corporation**  
 216 WEST FLORENCE AVENUE  
 INGLEWOOD, CALIFORNIA 90301  
 (213) 673-8422 • Telex 65-3474 • FAX (213) 672-2905

**CASE TO-66**  
 $I_C(\text{MAX}) = 1\text{-}5\text{A}$   
 $V_{\text{CEO(SUS)}} = 40\text{-}425\text{V}$

**PNP Power Transistors**

Type No.	NPN complement	V <sub>CEO</sub> (max) (V)	I <sub>C</sub> (max) (A)	h <sub>FE</sub> @I <sub>C</sub> /V <sub>CE</sub> (min-max @ A/V)	V <sub>CE(SAT)</sub> @ I <sub>C</sub> /I <sub>B</sub> (V @ A/A)	V <sub>BE</sub> @ I <sub>C</sub> /V <sub>CE</sub> (V @ A/V)	V <sub>BE (SAT)</sub> @ I <sub>C</sub> /I <sub>B</sub> (V @ A/A)	I <sub>CEV</sub> @ V <sub>CE</sub> (mA @ V)	P <sub>D</sub> @ TC = 100°C (Watts)	I <sub>sb</sub> @ V <sub>CE</sub> t = 1 sec (A @ V)	f <sub>r</sub> (MHz)	t <sub>on</sub> @ I <sub>C</sub> /I <sub>B</sub> (μs @ A/A)	t <sub>OFF</sub> @ I <sub>C</sub> /I <sub>B</sub> (μs @ A/A)
2N3740	2N3766	60	1	30-100 @ .25/1	.6 @ 1/1.25	1 @ .25/1		.1 @ 60	25	1.5 @ 17	4		
2N3740A		60	1	30-100 @ .25/1	.6 @ 1/1.25	1 @ .25/1		.0001 @ 60	25	1.5 @ 17	4		
2N3741	2N3767	80	1	30-100 @ .25/1	.6 @ 1/1.25	1 @ .25/1		.1 @ 80	25	1.5 @ 17	4		
2N3741A		80	1	30-100 @ .25/1	.6 @ 1/1.25	1 @ .25/1		.0001 @ 80	25	1.5 @ 17	4		
2N4898	2N4910	40	1	20-100 @ .5/1	.6 @ 1/1	1.3 @ 1/1		.1 @ 40	25	1.5 @ 17	3		
2N4899	2N4911	60	1	20-100 @ .5/1	.6 @ 1/1	1.3 @ 1/1		.1 @ 60	25	1.5 @ 17	3		
2N4900	2N4912	80	1	20-100 @ .5/1	.6 @ 1/1	1.3 @ 1/1		.1 @ 80	25	1.5 @ 17	3		
2N5344		250	1	25-100 @ .5/5	3 @ 1/1.2		1.5 @ 1/2	.1 @ 22	40	1 @ 22	10 <sup>6</sup>	.2 @ .5/0.5	.7 @ .5/0.5
2N5345		300	1	25-100 @ .5/5	3 @ 1/2		1.5 @ 1/2	.1 @ 270	40	1 @ 22	10 <sup>6</sup>	.2 @ .5/0.5	.7 @ .5/0.5
2N5954	2N6374	80	6	20-100 @ 2/4	1 @ 2/2	2 @ 2/4		.1 @ 85	40	1.75 @ 23	5	.7 @ 1.5/1.5	1.8 @ 1.5/1.5
2N5955	2N6373	80	6	20-100 @ 1.5/4	1 @ 2.5/2.5	2 @ 2.5/4		.1 @ 85	40	1.75 @ 23	5	.7 @ 1.5/1.5	1.8 @ 1.5/1.5
2N5956	2N6372	40	6	20-100 @ 3/4	1 @ 3/3	2 @ 3/4		.1 @ 45	40	1.75 @ 23	5	.7 @ 1.5/1.5	1.8 @ 1.5/1.5
2N6049	2N3054A	55	4	25-100 @ .5/4	.5 @ .5/0.5	1 @ .5/4			75	3 @ 25	3	.7 @ 1.5/1.5	1.8 @ 1.5/1.5
2N6211	2N3583	250 <sup>a</sup>	2	10-100 @ 1/2.8	1.4 @ 1/1.25		1.4 @ 1/1.25	.1 @ 90	35	.875 @ 40	20	.6 @ 1/1.25	3.1 @ 1/1.25
2N6212	2N3584	325 <sup>a</sup>	2	10-100 @ 1/3.2	1.6 @ 1/1.25		1.4 @ 1/1.25	.5 @ 250	35	.875 @ 40	20	.6 @ 1/1.25	3.1 @ 1/1.25
2N6213	2N3585	375 <sup>a</sup>	2	10-100 @ 1/4	2 @ 1/1.25		1.4 @ 1/1.25	.2 @ 360	35	.875 @ 40	20	.6 @ 1/1.25	3.1 @ 1/1.25
2N6214		425 <sup>a</sup>	2	10-100 @ 1/5	2.5 @ 1/1.25		1.4 @ 1/1.25	.5 @ 410	35	.875 @ 40	20	.6 @ 1/1.25	3.1 @ 1/1.25
2N6312	2N4232A	40	5	25-100 @ 1.5/4	.7 @ 1.5/1.5	1.4 @ 1.5/4		.1 @ 40	75	3 @ 25	4	.7 @ 1.5/1.5	1.8 @ 1.5/1.5
2N6313	2N4233A	60	5	25-100 @ 1.5/4	.7 @ 1.5/1.5	1.4 @ 1.5/4		.1 @ 60	75	3 @ 25	4	.7 @ 1.5/1.5	1.8 @ 1.5/1.5
2N6314	2N4233A	80	5	25-100 @ 1.5/4	.7 @ 1.5/1.5	1.4 @ 1.5/4		.1 @ 80	75	3 @ 25	4	.7 @ 1.5/1.5	1.8 @ 1.5/1.5
2N6317	2N6315	60	7	20-100 @ 2.5/4	1 @ 4/4	1.5 @ 2.5/4		.25 @ 60	90	3 @ 30	4	.7 @ 2.5/2.5	1.8 @ 2.5/2.5
2N6318	2N6316	80	7	20-100 @ 2.5/4	1 @ 4/4	1.5 @ 2.5/4		.25 @ 80	90	3 @ 30	4	.7 @ 2.5/2.5	1.8 @ 2.5/2.5

NOTES: h) V<sub>CE</sub> (V) i) (typical)

**CASE TO-59/TO-111**  
 $I_C(\text{MAX}) = 3\text{A}\text{-}10\text{A}$   
 $V_{\text{CEO(SUS)}} = 40\text{-}100\text{V}$

**NPN Power Transistors**

Type No.	V <sub>CEO</sub> (max) (V)	I <sub>C</sub> (max) (A)	h <sub>FE</sub> @I <sub>C</sub> /V <sub>CE</sub> (min-max @ A/V)	V <sub>CE(SAT)</sub> @ I <sub>C</sub> /I <sub>B</sub> (V @ A/A)	V <sub>BE</sub> @ I <sub>C</sub> /V <sub>CE</sub> (V @ A/V)	V <sub>BE (SAT)</sub> @ I <sub>C</sub> /I <sub>B</sub> (V @ A/V)	I <sub>CEV</sub> @ V <sub>CE</sub> (mA @ V)	P <sub>D</sub> @ TC = 25°C (Watts)	I <sub>sb</sub> @ V <sub>CE</sub> t = 1 sec (A @ V)	f <sub>r</sub> (MHz)	t <sub>on</sub> @ I <sub>C</sub> /I <sub>B</sub> (μs @ A/A)	t <sub>OFF</sub> @ I <sub>C</sub> /I <sub>B</sub> (μs @ A/A)
2N2877	50	5	20-60 @ 1/2	2 @ 5/5	1.2 @ 1/2		.01 @ 80	30	2.5 @ 12	30	.3 @ 1/1	1.5 @ 1/1
2N2878	50	5	40-120 @ 1/2	2 @ 5/5	1.2 @ 1/2		.01 @ 80	30	2.5 @ 12	50	.3 @ 1/1	1.5 @ 1/1
2N2879	70	5	20-60 @ 1/2	2 @ 5/5	1.2 @ 1/2		.01 @ 100	30	2.5 @ 12	30	.3 @ 1/1	1.5 @ 1/1
2N2880	70	5	40-120 @ 1/2	2 @ 5/5	1.2 @ 1/2		.01 @ 100	30	1.5 @ 12	50	.3 @ 1/1	1.5 @ 1/1
2N2892	80	5	30-90 @ 1/2	.75 @ 2/2		1.2 @ 1/1	.1 @ 100	17	3 @ 10	30	.3 @ 1/0.5	1.5 @ 1/0.5
2N2893	80	5	50-150 @ 1/2	.75 @ 2/2		1.2 @ 1/1	.1 @ 100	17	3 @ 10	30	.3 @ 1/0.5	1.5 @ 1/0.5
2N3850	80	5	50-150 @ 1/1	.5 @ 2/2		1.3 @ 2/2	.0001 @ 80	40		20	.2 @ 1/0.5	.9 @ 1/0.5
2N3851	80	5	30-90 @ 1/1	.5 @ 2/2		1.3 @ 2/2	.0001 @ 80	40		20	.2 @ 1/0.5	.9 @ 1/0.5
2N3852	40	5	50-150 @ 1/1	.5 @ 2/2		1.3 @ 2/2	.0001 @ 40	40		20	.2 @ 1/0.5	.9 @ 1/0.5
2N2853	40	5	30-90 @ 1/1	.5 @ 2/2		1.3 @ 2/2	.0001 @ 40	40		20	.2 @ 1/0.5	.9 @ 1/0.5
2N3998*	80	5	40-120 @ 1/2	2 @ 5/5		.6-1.2 @ 1/1	.005 @ 90	30	1.5 @ 20	40	.3 @ 1/1	1.5 @ 1/1
2N3999*	80	5	80-240 @ 1/2	2 @ 5/5		.6-1.2 @ 1/1	.005 @ 90	30	1.5 @ 20	40	.3 @ 1/1	2 @ 1/1
2N5477	80	7	30-120 @ 2/2	1.2 @ 7/7		1.2 @ 2/2	.01 @ 80	34	3 @ 20	30	.2 @ 2/2	2.2 @ 2/2
2N5478	80	7	60-240 @ 2/2	1.2 @ 7/7		1.2 @ 2/2	.01 @ 80	34		30	.2 @ 2/2	2.2 @ 2/2
2N5479	100	7	30-120 @ 2/2	1.2 @ 7/7		1.2 @ 2/2	.01 @ 100	34		30	.2 @ 2/2	2.2 @ 2/2
2N5480	100	7	60-240 @ 2/2	1.2 @ 7/7		1.2 @ 2/2	.01 @ 100	34		30	.2 @ 2/2	2.2 @ 2/2

NOTES: b) I<sub>CBO</sub> @ V<sub>CB</sub> (mA @ V) g) I<sub>CE</sub> @ V<sub>CE</sub> (mA @ V) i) (typical)

**General Transistor Corporation**

216 WEST FLORENCE AVENUE

INGLEWOOD, CALIFORNIA 90301

(213) 673-8422 • Telex 65-3474 • FAX (213) 672-2905

**PNP Power Transistors**

**CASE TO-5/TO-39**  
 **$I_{C(MAX)} = 0.05-5A$**   
 **$V_{CEO(SUS)} = 40-450V$**

Type No.	NPN complement	V <sub>CEO</sub> (max) (V)	I <sub>C</sub> (max) (A)	h <sub>FE</sub> @I <sub>C</sub> /V <sub>CE</sub> (min-max @ A/V)	V <sub>CE(SAT)</sub> @ I <sub>C</sub> /I <sub>B</sub> (V @ A/A)	V <sub>BE</sub> @ I <sub>C</sub> /V <sub>CE</sub> (V @ A/V)	I <sub>CEV</sub> @ V <sub>CE</sub> (mA @ V)	P <sub>D</sub> @ TC = 100°C (Watts)	C <sub>ob</sub> (pf)	f <sub>r</sub> (MHz)	t <sub>on</sub> @ I <sub>C</sub> /I <sub>B</sub> (μs @ A/A)	t <sub>OFF</sub> @ I <sub>C</sub> /I <sub>B</sub> (μs @ A/A)
2N3743	2N3742	300	.05	25-250 @ .03/10	8 @ .03/0.03	1.2 @ .03/0.03	.0003* @ 200	5	120	10*	.3 @ 1/1	1.2 @ 1/1
2N3867		40	3	>25 @ 2.5/3	1.3 @ 2.5/25	2.2 @ 2.5/25	.001 @ 40	6	120	60	.3 @ 1/1	1.2 @ 1/1
2N3868		60	3	>25 @ 2.5/3	1.3 @ 2.5/25	2.2 @ 2.5/25	.001 @ 60	6	120	60	.3 @ 1/1	1.2 @ 1/1
2N4930	2N4928	200	.05	20-200 @ .01/10	5 @ .01/0.01	1 @ .01/10	.1* @ 200	5	20	10*		
2N4931	2N4927	250	.05	20-200 @ .01/10	5 @ .01/0.01	1 @ .01/10	.1* @ 250	5	20	10*		
2N5091		300	1	20-200 @ .1/15	3 @ .025/0.025	1 @ .025/10	.1* @ 350	4	20	10*		
2N5093	2N5092	350	1	20-200 @ .1/15	3 @ .025/0.025	1 @ .025/10	.1* @ 400	4	20	10*		
2N5094	2N5095	400	1	20-200 @ .1/15	3 @ .025/0.025	1 @ .025/10	.1* @ 450	4	20	10*		
2N5096	2N5097	450	1	20-200 @ .1/15	3 @ .025/0.025	1 @ .025/10	.1* @ 500	4	20	10*	.3 @ 1/1	1.2 @ 1/1
2N5147	2N5148	80	2	30-90 @ 1/5	.85 @ 2/2	1.5 @ 2/5	1 @ 100	6	120	50	.3 @ 1/1	1.2 @ 1/1
2N5149	2N5150	80	5	70-200 @ 1/5	.85 @ 2/2	1.5 @ 2/5	1 @ 100	6	120	60	.3 @ 1/1	1.2 @ 1/1
2N5151	2N5152	80	5	30-90 @ 2.5/5	.75 @ 2.5/25	1.45 @ 2.5/5	1 @ 100	10	250	60	.3 @ 1/1	1.2 @ 1/1
2N5153	2N5154	80	5	70-200 @ 2.5/5	.75 @ 2.5/25	1.45 @ 2.5/5	1 @ 100	10	250	60	.3 @ 1/1	1.2 @ 1/1
2N5415	2N3440	200	1	30-150 @ .05/10	2.5 @ .05/0.05	1.5 @ .05/10	.05 @ 200	10	15	15		
2N5416	2N3439	300	1	30-150 @ .05/10	2 @ .05/0.05	1.5 @ .05/10	.05 @ 300	10	15	15		

NOTES: b) I<sub>CB0</sub> @ V<sub>CB</sub> (mA @ V) c) V<sub>BE(SAT)</sub> @ I<sub>C</sub>/I<sub>B</sub> (V @ A/A) d) (typical)

**NPN Power Transistors**

**CASE TO-8**  
 **$I_{C(MAX)} = 1-3A$**   
 **$V_{CEO(SUS)} = 40-55V$**

Type No.	V <sub>CEO</sub> (max) (V)	I <sub>C</sub> (max) (A)	h <sub>FE</sub> @I <sub>C</sub> /V <sub>CE</sub> (min-max @ A/V)	V <sub>CE(SAT)</sub> @ I <sub>C</sub> /I <sub>B</sub> (V @ A/A)	V <sub>BE</sub> @ I <sub>C</sub> /V <sub>CE</sub> (V @ A/V)	I <sub>CEV</sub> @ V <sub>CE</sub> (mA @ V)	P <sub>D</sub> @ TC = 25°C (Watts)	I <sub>e/b</sub> @V <sub>CE</sub> t = 1 sec (A @ V)	f <sub>r</sub> (MHz)	t <sub>on</sub> @ I <sub>C</sub> /I <sub>B</sub> (μs @ A/A)	t <sub>OFF</sub> @ I <sub>C</sub> /I <sub>B</sub> (μs @ A/A)
2N1483	40	3	20-60 @ .75/4	2 @ .75/0.75	3.5 @ .75/4	.015* @ 30	25	1* @ 25	1.25	.3 @ 1/1	6 @ 1/1
2N1484	55	3	20-60 @ .75/4	2 @ .75/0.75	3.5 @ .75/4	.015* @ 30	25	1* @ 25	1.25	.3 @ 1/1	6 @ 1/1
2N1495	40	3	35-100 @ .75/4	.75 @ .75/4	2.5 @ .75/4	.015* @ 30	25	1* @ 25	1.25	.3 @ 1/1	6 @ 1/1
2N1486	55	3	35-100 @ .75/4	2.5 @ .75/4	2.5 @ .75/4	.015* @ 30	25	1* @ 25	1.25	.3 @ 1/1	6 @ 1/1
2N1701	40	2.5	20-80 @ 3/4	3 @ .3/4	3 @ .3/4	.75* @ 60	25	1* @ 25	0.35	.3 @ 1/1	6 @ 1/1

NOTES: b) I<sub>CB0</sub> @ V<sub>CB</sub> (mA @ V) d) (typical)

General Transistor Corporation  
 216 WEST FLORENCE AVENUE  
 INGLEWOOD, CALIFORNIA 90301  
 (213) 673-8422 • Telex 65-3474 • FAX (213) 672-2905

**CASE TO-61**  
 $I_C(\text{MAX}) = 5 \text{ to } 20\text{A}$   
 $V_{CEO(\text{SUS})} = 40\text{-}300\text{V}$

**NPN Power Transistors**

Type No.	V <sub>CEO</sub> (min) (V)	I <sub>C</sub> (max) (A)	h <sub>FE</sub> (I <sub>C</sub> /V <sub>CE</sub> ) (min-max @ A/V)	V <sub>CE(SAT)</sub> @ I <sub>C</sub> /I <sub>B</sub> (V @ A/A)	V <sub>BE</sub> @ I <sub>C</sub> /V <sub>CE</sub> (V @ A/V)	V <sub>BE(SAT)</sub> @ I <sub>C</sub> /I <sub>B</sub> (V @ A/V)	I <sub>CEV</sub> @ V <sub>CE</sub> (mA @ V)	P <sub>D</sub> @ T <sub>C</sub> = 25°C (Watts)	I <sub>sat</sub> @ V <sub>CE</sub> I = 1 sec (A @ V)	f <sub>r</sub> (MHz)	t <sub>on</sub> @ I <sub>C</sub> /I <sub>B</sub> (μs @ A/A)	t <sub>OFF</sub> @ I <sub>C</sub> /I <sub>B</sub> (μs @ A/A)
2N1724	80	5	20-90 @ 2/15	1 @ 2/2		2 @ 2/2	10 <sup>4</sup> @ 120	50	1.25 @ 40	10	.3 @ 5/5	1.5 @ 5/5
2N1724A	120	5	30-90 @ 2/15	.5 @ 2/2		1.2 @ 2/2	10 <sup>4</sup> @ 180	50	1.25 @ 40	10	.3 @ 5/5	1.5 @ 5/5
2N1725	80	5	50-150 @ 2/15	1 @ 2/2		2 @ 2/2	10 <sup>4</sup> @ 120	50	1.25 @ 40	10	.3 @ 5/5	1.5 @ 5/5
2N2811	50	10	20-80 @ 5/5	.5 @ 5/5		1.2 @ 5/5	.01 @ 80	40	1.25 @ 40	15	.3 @ 5/5	1.5 @ 5/5
2N2812	50	10	40-120 @ 5/5	.5 @ 5/5		1.2 @ 5/5	.01 @ 80	40	1.25 @ 40	15	.3 @ 5/5	1.5 @ 5/5
2N2813	70	10	20-60 @ 5/5	.5 @ 5/5		1.2 @ 5/5	.01 @ 120	40	1.25 @ 40	15	.3 @ 5/5	1.5 @ 5/5
2N2814	70	10	40-120 @ 5/5	.5 @ 5/5		1.2 @ 5/5	.01 @ 120	40	1.25 @ 40	15	.3 @ 5/5	1.5 @ 5/5
2N3487	60	7.5	20-60 @ 3/5	1.2 @ 3/3	1.5 @ 3/5		.1 @ 80	67	7.5 @ 15.6	10	.35 @ 5/5	2.35 @ 5/5
2N3488	80	7.5	20-60 @ 3/5	1.2 @ 3/3	1.5 @ 3/5		.1 @ 100	67	7.5 @ 15.6	10	.35 @ 5/5	2.35 @ 5/5
2N3489	100	7.5	15-45 @ 3/5	1.2 @ 3/3	1.5 @ 3/5		.1 @ 120	67	7.5 @ 15.6	10	.35 @ 5/5	2.35 @ 5/5
2N3490	60	7.5	40-120 @ 5/5	1.5 @ 5/5	1.4 @ 5/5		.1 @ 80	67	7.5 @ 15.6	10	.35 @ 5/5	2.35 @ 5/5
2N3491	80	7.5	40-120 @ 5/5	1.5 @ 5/5	1.4 @ 5/5		.1 @ 100	67	7.5 @ 15.6	10	.35 @ 5/5	2.35 @ 5/5
2N3492	100	7.5	30-90 @ 5/5	1.5 @ 5/5	1.4 @ 5/5		.1 @ 120	67	7.5 @ 15.6	10	.35 @ 5/5	2.35 @ 5/5
2N3597	40	20	40-120 @ 10/2	1.5 @ 20/2	1.2 @ 10/2		.01 @ 60	100	4 @ 25	30	.7 @ 10/1	2.7 @ 10/1
2N3598	60	20	40-120 @ 10/2	1.5 @ 20/2	1.2 @ 10/2		.1 @ 80	100	4 @ 25	30	.7 @ 10/1	2.7 @ 10/1
2N3599	80	20	40-120 @ 10/2	1.5 @ 20/2	1.2 @ 10/2		.01 @ 100	100	4 @ 25	30	.7 @ 10/1	2.7 @ 10/1
2N4301	80	10	30-120 @ 5/4	.4 @ 5/5	1.2 @ 10/4		.01 @ 90	50	3 @ 16.7	40	.5 @ 10/1	1.5 @ 10/1
2N5048	100	10	15-60 @ 10/4	2 @ 10/1		3 @ 10/1	1 @ 120	50	1 @ 50	10	.6 @ 10/1.5	2.1 @ 10/1.5
2N5049	50	10	15-60 @ 10/4	2.5 @ 10/1		3 @ 10/1	10 <sup>4</sup> @ 60	50	1 @ 50	10	1 @ 10/1.5	3.5 @ 10/1.5
2N5218	200	10	15-120 @ 5/5	.6 @ 5/5	1.2 @ 5/5		.01 @ 220	50	1.43 @ 35	40	.6 @ 1/1	5.5 @ 1/1
2N5313	80	10	30-90 @ 10/5	1.5 @ 10/1		1.5 @ 10/1	.01 @ 80	50	2.5 @ 20	30	.5 @ 10/1	1.5 @ 10/1
2N5315	100	10	30-90 @ 10/5	1.5 @ 10/1		1.5 @ 10/1	.01 @ 100	50	2.5 @ 20	30	.5 @ 10/1	1.5 @ 10/1
2N5387	200	7.5	25-100 @ 2/5	2.2 @ 7/1.4	2.5 @ 7/5		1 @ 180	100	5 @ 20	15	1.5 @ 5/5	3 @ 5/5
2N5388	250	7.5	25-100 @ 2/5	2.2 @ 7/1.4	2.5 @ 7/5		1 @ 225	100	5 @ 20	15	1.5 @ 5/5	3 @ 5/5
2N5389	300	7.5	25-100 @ 2/5	2.2 @ 7/1.4	2.5 @ 7/5		1 @ 270	100	2 @ 20	15	1.5 @ 5/5	3 @ 5/5
2N5540	300	10	20-60 @ 5/5	1 @ 8/8		1.2 @ 5/5	.1 @ 325	50	.83 @ 60	20	1.5 @ 5/5	3 @ 5/5
2N5542	130	10	30-90 @ 5/5	.5 @ 5/5		1.2 @ 5/5	.01 @ 175	50	5 @ 10	20	.5 @ 5/5	2 @ 5/5
2N5959	100	20	30-120 @ 10/10	.4 @ 5/5		2 @ 20/2	.5 @ 100	100	4 @ 25	10	.5 @ 20/2	1 @ 20/2
2N6562	450	10	10-40 @ 5/2	.75 @ 5/1		1.4 @ 5/1	1 @ 450	125	2.8 @ 45	10	.6 @ 5/1	3 @ 5/1
2N6563	300	10	10-50 @ 10/2	.75 @ 10/2		1.8 @ 10/2	1 @ 300	100	2 @ 50	15	.6 @ 5/1	1.7 @ 5/1
2N6585	350	10	7-35 @ 5/3	3 @ 10/5		1.5 @ 5/1	.5 @ 450	125	.09 @ 200	12.5	.55 @ 5/1	2.5 @ 5/1
2N6586	400	10	7-35 @ 5/3	3 @ 10/5		1.5 @ 5/1	.5 @ 500	125	.09 @ 200	12.5	.55 @ 5/1	2.5 @ 5/1
2N6587	450	10	7-35 @ 5/3	3 @ 10/5		1.5 @ 5/1	.5 @ 550	125	.09 @ 200	12.5	.55 @ 5/1	2.5 @ 5/1
2N6588	350	10	7-35 @ 5/3	3 @ 10/5		1.5 @ 7/1.4	.5 @ 450	125	.09 @ 200	12.5	.55 @ 7/1.4	2.5 @ 7/1.4
2N6589	400	10	7-35 @ 5/3	3 @ 10/5		1.5 @ 7/1.4	.5 @ 500	125	.09 @ 200	12.5	.55 @ 7/1.4	2.5 @ 7/1.4
2N6590	450	10	7-35 @ 5/3	3 @ 10/5		1.5 @ 7/1.4	.5 @ 550	125	.09 @ 200	12.5	.55 @ 7/1.4	2.5 @ 7/1.4
2N6689	300	15	>8 @ 10/2	1 @ 10/2		1.5 @ 10/2	.1 @ 450	175	5 @ 20	15	.7 @ 10/2	3 @ 10/1
2N6690	400	15	>8 @ 10/2	1 @ 10/2		1.5 @ 10/2	.1 @ 650	175	5 @ 20	15	.7 @ 10/2	3 @ 10/1
2N6691	300	15	>8 @ 15/3	1 @ 15/3		1.5 @ 15/3	.1 @ 450	175	5 @ 20	15	.7 @ 15/3	3 @ 15/3
2N6692	350	15	>8 @ 15/3	1 @ 15/3		1.5 @ 15/3	.1 @ 550	175	5 @ 20	15	.7 @ 15/3	3 @ 15/3
2N6693	400	15	>8 @ 15/3	1 @ 15/3		1.5 @ 15/3	.1 @ 650	175	5 @ 20	15	.7 @ 15/3	3 @ 15/3

NOTES: b) I<sub>CB0</sub> @ V<sub>CB</sub> (mA @ V) g) I<sub>CES</sub> @ V<sub>CE</sub> (mA @ V) h) (typical)