


Power Transistors

TO-126 Case



TYPE NO.		I_C (A)	P_D (W)	V_{CBO} (V)	V_{CEO} (V)	h_{FE}		@ I_C (mA)	$V_{CE(SAT)}$ (V)	@ I_C (A)	f_T (MHz)
NPN	PNP	MAX		MIN	MIN	MIN	MAX		MAX		MIN
2N4921	2N4918	1.0	30	40	40	30	150	500	0.6	1.0	3.0
2N4922	2N4919	1.0	30	60	60	30	150	500	0.6	1.0	3.0
2N4923	2N4920	1.0	30	80	80	30	150	500	0.6	1.0	3.0
2N5190	2N5193	4.0	40	40	40	25	100	1,500	0.6	1.5	2.0
2N5191	2N5194	4.0	40	60	60	25	100	1,500	0.6	1.5	2.0
2N5192	2N5195	4.0	40	80	80	20	80	1,500	0.6	1.5	2.0
2N5655		0.5	20	275	250	30	250	100	1.0	0.1	10
2N5656		0.5	20	325	300	30	250	100	1.0	0.1	10
2N5657		0.5	20	375	350	30	250	100	1.0	0.1	10
2N6037	2N6034	4.0	40	40	40	750	15,000	2,000	2.0	2.0	25
2N6038	2N6035	4.0	40	60	60	750	15,000	2,000	2.0	2.0	25
2N6039	2N6036	4.0	40	80	80	750	15,000	2,000	2.0	2.0	25
BD135	BD136	1.5	12.5	45	45	63	250	150	0.5	0.5	--
BD137	BD138	1.5	12.5	60	60	63	250	150	0.5	0.5	--
BD139	BD140	1.5	12.5	100	80	63	250	150	0.5	0.5	--
BD175	BD176	3.0	30	45	45	40	--	150	0.8	1.0	3.0
BD177	BD178	3.0	30	60	60	40	--	150	0.8	1.0	3.0
BD179	BD180	3.0	30	80	80	40	--	150	0.8	1.0	3.0
BD233	BD234	2.0	25	45	45	40	--	150	0.6	1.0	3.0
BD235	BD236	2.0	25	60	60	40	--	150	0.6	1.0	3.0
BD237	BD238	2.0	25	80	80	40	--	150	0.6	1.0	3.0
BD433	BD434	4.0	36	22	22	40	--	10	0.5	2.0	3.0
BD435	BD436	4.0	36	32	32	40	--	10	0.5	2.0	3.0
BD437	BD438	4.0	36	45	45	30	--	10	0.6	2.0	3.0
BD439	BD440	4.0	36	60	60	20	--	10	0.8	2.0	3.0
BD441	BD442	4.0	36	80	80	15	--	10	0.8	2.0	3.0
BD675	BD676	4.0	40	45	45	750	--	1.5	2.5	1.5	1.0
BD675A	BD676A	4.0	40	45	45	750	--	2.0	2.8	2.0	1.0
BD677	BD678	4.0	40	60	60	750	--	1.5	2.5	1.5	1.0
BD677A	BD678A	4.0	40	60	60	750	--	2.0	2.8	2.0	1.0
BD679	BD680	4.0	40	80	80	750	--	1.5	2.5	1.5	1.0
BD679A	BD680A	4.0	40	80	80	750	--	2.0	2.8	2.0	1.0
BD681	BD682	4.0	40	100	100	750	--	1.5	2.5	1.5	1.0
BD683	BD684	4.0	40	120	120	750	--	1.5	2.5	1.5	1.0
BF469	BF470	0.05	1.25	250	250	50	--	0.025	0.6	0.03	60
BF471	BF472	0.05	1.25	300	300	50	--	0.025	0.6	0.03	60

Shaded areas indicate Darlington.

(6-December 2004)