



1 Amp. Surface Mounted Glass Passivated Ultrafast Recovery Rectifier


<p>Dimensions in mm.</p>  <p>XXX = Marking code WW = Week code Y = Year code</p>	<p style="text-align: center;">CASE: M1F (DO219AA)</p> <p style="text-align: center;">Voltage 50 to 600 V</p> <p style="text-align: center;">Current 1.0 A</p> <div style="text-align: center; color: red; font-weight: bold; margin: 10px 0;">  </div> <ul style="list-style-type: none"> For surface mounted application Low profile package Low power loss, high efficiency, Ideal for automated placement Glass Passivated chip junction High temperature soldering: 260 °C / 10 seconds at terminals <p>MECHANICAL DATA</p> <ul style="list-style-type: none"> Case: Sub SMA plastic case Terminal: Pure tin plated, lead free. Polarity: Color band cathode end Packaging: 12 mm. tape per EIA STD RS-481 Weight: 0.015 g.
---	--

Maximun Ratings and Electrical Characteristics at 25 °C


Marking Code		FES1AL	FES1BL	FES1CL	FES1DL	FES1FL	FES1GL	FES1HL	FES1JL
Marking Code		EAL	EBL	ECL	EDL	EFL	EGL	EHL	EJL
V_{RRM}	Maximum Recurrent Peak Reverse Voltage (V)	50	100	150	200	300	400	500	600
V_{RMS}	Maximum RMS Voltage (V)	35	70	105	140	210	280	350	420
V_{DC}	Maximum DC Blocking Voltage (V)	50	100	150	200	300	400	500	600
$I_{F(AV)}$	Forward current at $T_L = 120\text{ °C}$	1.0 A							
I_{FSM}	8.3 ms. peak forward surge current (Jedec Method)	30 A							
V_F	Maximum Instantaneous Forward Voltage at 1.0A	0.95 V			1.3 V		1.7 V		
I_R	Maximum DC Reverse Current at Rated DC Blocking Voltage	$T_a = 25\text{ °C}$ 5 μ A				$T_a = 100\text{ °C}$ 100 μ A			
T_{rr}	Maximum Reverse Recovery Time (0.5/1/0.25A)	35 nS							
C_j	Typical Junction Capacitance (1MHz; -4V)	10 pF				8 pF			
$R_{th(j-l)}$	Maximum Thermal Resistance	85 °C/W							
$R_{th(j-a)}$	(5x5 mm ² x 130 μ Copper Area)	35 °C/W							
$T_j - T_{stg}$	Operating Junction and Storage Temperature Range	-55 to + 150 °C							

Rating And Characteristic Curves


MAXIMUM FORWARD CURRENT DERATING CURVE




TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS




MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT



TYPICAL JUNCTION CAPACITANCE



TYPICAL REVERSE CHARACTERISTICS



REVERSE RECOVERY TIME CHARACTERISTIC AND TEST CIRCUIT DIAGRAM

