

# Medium Power Amplifiers and Switches

TYPE NO.	POLARITY	CASE	MAXIMUM RATINGS			H <sub>FE</sub>		V <sub>CE(sat)</sub>		f <sub>T</sub> min	C <sub>ob</sub> max	COMPLEMENTARY TYPE		
			P <sub>d</sub> (mW)	I <sub>C</sub> (A)	V <sub>CEO</sub> V <sub>CER</sub> * (V)	min	max	I <sub>C</sub> (mA)	V <sub>CE</sub> (V)				max (V)	I <sub>C</sub> (A)
2N3299	N	TO-39	800	0.5	30	40	120	150	10	0.6	0.5	250	8	-
2N3300	N	TO-39	800	0.5	30	100	300	150	10	0.6	0.5	250	8	-
2N3301	N	TO-18	360	0.5	30	40	120	150	10	0.6	0.5	250	8	-
2N3302	N	TO-18	360	0.5	30	100	300	150	10	0.6	0.5	250	8	-
2N3326	N	TO-39	800	0.8	45	40	120	150	10	0.6	0.5	250	8	-
2N3414	N	TO-92B	360	0.5	25	75	225	2	4.5	0.3	0.05	-	-	-
2N3415	N	TO-92B	360	0.5	25	180	540	2	4.5	0.3	0.05	-	-	-
2N3416	N	TO-92B	360	0.5	50	75	225	2	4.5	0.3	0.05	-	-	-
2N3417	N	TO-92B	360	0.5	50	180	540	2	4.5	0.3	0.05	-	-	-
2N3502	P	TO-39	800	0.6	45	100	300	150	10	1	0.3	200	8	-
2N3503	P	TO-39	800	0.6	60	100	300	150	10	1	0.3	200	8	-
2N3504	P	TO-18	400	0.6	45	100	300	150	10	1	0.3	200	8	-
2N3505	P	TO-18	400	0.6	60	100	300	150	10	1	0.3	200	8	-
2N3678	N	TO-39	800	0.8	55	40	120	150	10	1	0.5	250	8	-
2N3700	N	TO-18	500	1	80	100	300	150	10	0.5	0.5	100	12	-
2N3701	N	TO-18	500	1	80	40	120	150	10	0.5	0.5	80	12	-
2N3702	P	TO-92B	360	0.2	25	60	300	50	5	0.25	0.05	100	12	2N3704
2N3703	P	TO-92B	360	0.2	30	30	150	50	5	0.25	0.05	100	12	2N3706
2N3704	N	TO-92B	360	0.2	30	100	300	50	2	0.6	0.1	100	12	2N3702
2N3705	N	TO-92B	360	0.2	30	50	150	50	2	0.8	0.1	100	12	2N3702
2N3706	N	TO-92B	360	0.2	20	30	600	50	2	1	0.1	100	12	2N3703
2N3793	N	TO-92B	250	0.5	20	20	120	10	10	0.4	0.1	100	10	-
2N3794	N	TO-92B	250	0.5	20	100	600	10	10	0.4	0.1	100	10	-
2N3945	N	TO-39	5000 //	1	50	40	250	150	10	0.5	0.15	60	12	-
2N4029	P	TO-18	500	1	80	100	300	100	5	0.5	0.5	150+	20	-
2N4030	P	TO-39	800	1	60	40	120	100	5	0.5	0.5	100	20	2N3108
2N4031	P	TO-39	800	1	80	40	120	100	5	0.5	0.5	100	20	2N3020
2N4032	P	TO-39	800	1	60	100	300	100	5	0.5	0.5	150	20	2N3107
2N4033	P	TO-39	800	1	80	100	300	100	5	0.5	0.5	150	20	2N3109
2N4036	P	TO-39	1000	1	65	40	140	150	10	0.65	0.15	60	30	2N2102
2N4037	P	TO-39	1000	1	40	50	250	150	10	1.4	0.15	60	30	2N3053
2N4234	P	TO-39	1000	3	40	30	150	250	1	0.6	1	3	100	2N4237
2N4235	P	TO-39	1000	3	60	30	150	250	1	0.6	1	3	100	2N4238
2N4236	P	TO-39	1000	1	80	30	150	250	1	0.6	1	3	100	2N4239
2N4237	N	TO-39	1000	1	40	30	150	250	1	0.6	1	2	100	2N4234
2N4238	N	TO-39	1000	1	60	30	150	250	1	0.6	1	2	100	2N4235
2N4239	N	TO-39	1000	1	80	30	150	250	1	0.3	0.5	2	100	2N4236
2N4314	P	TO-39	1000	1	65	50	250	150	10	1.4	0.15	60	30	-
2N4400	N	TO-92A	500	0.6	40	50	150	150	1	0.75	0.5	200	6.5	2N4402
2N4401	N	TO-92A	500	0.6	40	100	300	150	1	0.75	0.5	250	6.5	2N4403
2N4402	P	TO-92A	500	0.6	40	50	150	150	1	0.75	0.5	150	8.5	2N4400
2N4403	P	TO-92A	500	0.6	40	100	300	150	1	0.75	0.5	200	8.5	2N4401
2N4409	N	TO-92A	625	0.25	50	60	400	10	1	0.2	0.001	60	12	-
2N4424	N	TO-92B	625	0.5	40	180	540	2	4.5	0.3	0.05	-	-	-
2N4951	N	TO-92B	360	0.5	30	60	200	150	10	0.3	0.15	250	8	-
2N4952	N	TO-92B	360	0.5	30	100	300	150	10	0.3	0.15	250	8	-
2N4953	N	TO-92B	360	0.5	30	200	600	150	10	0.3	0.15	250	8	-
2N4954	N	TO-92B	360	0.5	30	60	600	150	10	0.3	0.15	250	8	-