



JAN Qualified N-Channel 60-V (D-S) MOSFETs

PRODUCT SUMMARY			
$V_{(BR)DSS}$ Min (V)	$r_{DS(on)}$ Max (Ω)	$V_{GS(th)}$ (V)	I_D (A)
60	3 @ $V_{GS} = 10$ V	0.8 to 2	0.99

FEATURES

- Military Qualified
- Low On-Resistance: 1.3 Ω
- Low Threshold: 1.7 V
- Low Input Capacitance: 35 pF
- Fast Switching Speed: 8 ns
- Low Input and Output Leakage


BENEFITS

- Guaranteed Reliability
- Low Offset Voltage
- Low-Voltage Operation
- Easily Driven Without Buffer
- High-Speed Circuits
- Low Error Voltage


APPLICATIONS

- Military Applications
- Direct Logic-Level Interface: TTL/CMOS
- Drivers: Relays, Solenoids, Lamps, Hammers, Displays, Memories, Transistors, etc.
- Battery Operated Systems
- Solid-State Relays

Datasheet.Directory



Device Marking
Side View



"S" = Siliconix Logo
f = Factory Code
// = Lot Traceability
xyxy = Date Code

*Note: or JANTX2N6660
JANTXV2N6660

ABSOLUTE MAXIMUM RATINGS ($T_A = 25^\circ\text{C}$ UNLESS OTHERWISE NOTED)			
Parameter	Symbol	Limit	Unit
Drain-Source Voltage	V_{DS}	60	V
Gate-Source Voltage	V_{GS}	± 20	
Continuous Drain Current ($T_J = 150^\circ\text{C}$)	I_D	$T_C = 25^\circ\text{C}$	A
		$T_C = 100^\circ\text{C}$	
Pulsed Drain Current ^a	I_{DM}	3	
Power Dissipation	P_D	$T_C = 25^\circ\text{C}$	W
		$T_A = 25^\circ\text{C}$	
Thermal Resistance, Junction-to-Ambient ^b	R_{thJA}	170	$^\circ\text{C/W}$
Thermal Resistance, Junction-to-Case	R_{thJC}	20	
Operating Junction and Storage Temperature Range	T_J, T_{stg}	-55 to 150	$^\circ\text{C}$

Notes

- a. Pulse width limited by maximum junction temperature.
- b. Not required by Military Spec.

SPECIFICATIONS ^a							
Parameter	Symbol	Test Conditions	Limits			Unit	
			Min	Typ ^b	Max		
Static							
Drain-Source Breakdown Voltage	$V_{(BR)DSS}$	$V_{GS} = 0\text{ V}, I_D = 10\ \mu\text{A}$	60	75		V	
Gate-Threshold Voltage	$V_{GS(th)}$	$V_{DS} = V_{GS}, I_D = 1\text{ mA}$		0.8	1.7		2
			$T_C = -55^\circ\text{C}$				2.5
Gate-Body Leakage	I_{GSS}	$V_{DS} = 0\text{ V}, V_{GS} = \pm 20\text{ V}$				± 100	
			$T_C = 125^\circ\text{C}$			± 500	
Zero Gate Voltage Drain Current	I_{DSS}	$V_{DS} = 48\text{ V}, V_{GS} = 0\text{ V}$				1	
			$T_C = 125^\circ\text{C}$			100	
On-State Drain Current ^c	$I_{D(on)}$	$V_{DS} = 10\text{ V}, V_{GS} = 10\text{ V}$		2		A	
Drain-Source On-Resistance ^c	$r_{DS(on)}$	$V_{GS} = 5\text{ V}, I_D = 0.3\text{ A}$		2	5	Ω	
			$V_{GS} = 10\text{ V}, I_D = 1\text{ A}$		1.3		3
			$T_C = 125^\circ\text{C}$		2.4		5.6
Forward Transconductance ^c	g_{fs}	$V_{DS} = 7.5\text{ V}, I_D = 0.525\text{ A}$	170	350		mS	
Diode Forward Voltage	V_{SD}	$I_S = 0.99\text{ A}, V_{GS} = 0\text{ V}$	0.7	0.8	1.6	V	
Dynamic							
Input Capacitance	C_{iss}	$V_{DS} = 25\text{ V}, V_{GS} = 0\text{ V}$ $f = 1\text{ MHz}$		35	50	pF	
Output Capacitance	C_{oss}			25	40		
Reverse Transfer Capacitance	C_{rss}			7	10		
Drain-Source Capacitance	C_{ds}			30			
Switching^d							
Turn-On Time	t_{ON}	$V_{DD} = 25\text{ V}, R_L = 23\ \Omega$ $I_D \cong 1\text{ A}, V_{GEN} = 10\text{ V}$ $R_G = 25\ \Omega$		8	10	ns	
Turn-Off Time	t_{OFF}			8.5	10		

Notes

- $T_A = 25^\circ\text{C}$ unless otherwise noted.
- For DESIGN AID ONLY, not subject to production testing.
- Pulse test: $PW \leq 300\ \mu\text{s}$ duty cycle $\leq 2\%$.
- Switching time is essentially independent of operating temperature.
- For typical characteristics curves see the 2N6659/2N6660, VQ1004J/P data sheet.

VNDQ06



Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.