

JEDEC No.	Type	Use	MAXIMUM RATINGS				ELECTRICAL PARAMETERS					Closest GE	Dwg. No.	
			P _C mw @ 25°C	BV _{CE} BV _{CB} *	I _C ma	T _J °C	MIN. h _{FE} -h _{FE} * @ I _C ma	MIN. f _{hfb} mc	MIN. G _e db	MAX. I _{CO} (μa)	@ V _{CB}			
2N3184	PNP	AF	75W		-5A		10*	-2A						
2N3185	PNP	AF	75W		-5A		10*	-2A						
2N3186	PNP	AF	75W		-5A		10*	-2A						
2N3187	PNP	AF	85W		-5A		10*	-3A						
2N3188	PNP	AF	85W		-5A		10*	-3A						
2N3189	PNP	AF	85W		-5A		10*	-3A						
2N3190	PNP	AF	85W		-5A		10*	-3A						
2N3191	PNP	AF	85W		-5A		10*	-3A						
2N3192	PNP	AF	85W		-5A		10*	-3A						
2N3193	PNP	AF	85W		-5A		10*	-3A						
2N3194	PNP	AF	85W		-5A		10*	-3A						
2N3195	PNP	AF	75W		-5A		10*	-3A						
2N3196	PNP	AF	75W		-5A		10*	-3A						
2N3197	PNP	AF	75W		-5A		10*	-3A						
2N3198	PNP	AF	75W		-5A		10*	-3A						
2N3199	PNP	AF	40W		-3A		20*	-1A						
2N3200	PNP	AF	40W		-3A		20*	-1A						
2N3201	PNP	AF	40W		-3A		20*	-1A						
2N3202	PNP	AF	8.75W		-3A		20*	-1A						
2N3203	PNP	AF	8.75W		-3A		20*	-1A						
2N3204	PNP	AF	8.75W		-3A		20*	-1A						
2N3205	PNP	AF	40W		-2A		20*	-500						
2N3206	PNP	AF	40W		-2A		20*	-500						
2N3207	PNP	AF	40W		-2A		20*	-500						
2N3208	PNP	AF	8.75W		-2A		20*	-500						
2N3209	PNP	Sw	1.2W	-20*	200	200	15*	100						
2N3210	NPN	Sw	1.2W	40*	500	200	30*	10			10 na	20	2N708	16
2N3211	NPN	Sw	1.2W	40*	500	200	10*	500						
2N3212	PNP	Sw	12.1W		5A		30*	-5A -3A						
2N3213	PNP	Sw	12.1W		5A		30*	-5A -3A						
2N3214	PNP	Sw	12.1W		5A		30*	-5A -3A						
2N3215	PNP	Sw	12.1W		5A		25*	-5A -3A						
2N3217	PNP	Sw			100						.001	15		
2N3218	PNP	Sw			100						.001	25		
2N3219	PNP	Sw			100						.001	40		
2N3220	NPN	AF			2A		20*	1A					2N3220	15
2N3221	NPN	AF			2A		40*	1A					2N3221	15
2N3222	NPN	AF			2A		20*	1A					2N3222	15