

JEDEC No.	Type	Use	MAXIMUM RATINGS				ELECTRICAL PARAMETERS					Closest GE	Dwg. No.	
			P _c mw @ 25°C	BV _{ce} BV _{CB} *	I _c ma	T _j °C	MIN. h _{fe} -h _{FE} * @ I _c ma	MIN. f _{hfb} mc	MIN. G _e db	MAX. I _{co} (μa) @ V _{CB}				
2N911	NPN-PL		500	100		200J	50T							
2N912	NPN-PL		500	100		200J	30T							
2N914	NPN-PEP	Sw	360	40		200J	30T						2N914	16
2N915	NPN-PL	AF	360	70		200J	40T						2N915	16
2N916	NPN-PL	AF	360	45		200J	50T						2N916	16
2N929	NPN-PL		300	45		175J	40						2N915	16
2N930	NPN-PL		300	45		175J	100						2N915	16
2N956	NPN-PL		500	75		200J	100T						2N956	16
2N960	PNP	Sw	150	15		100	20T							
2N961	PNP-EM	Sw	150	12		100	20T							
2N962	PNP-EM	Sw	150	12		100	20T							
2N964	PNP-EM	Sw	150	15		100	40T*							
2N965	PNP-EM	Sw	150	12		100	40T*							
2N966	PNP-EM	Sw	150	12		100	40T*							
2N968	PNP		150	15		100J	20T*							
2N969	PNP		150	12		100	20T*							
2N970	PNP		150	12		100	20T*							
2N971	PNP		150	7.0		100	20T*							
2N972	PNP		150	15		100	40T*							
2N973	PNP		150	12		100	40T*							
2N974	PNP		150	12		100	40T*							
2N975	PNP		150	7.0		100	40T*							
2N994	PNP	Sw	200	15		150S	75*							
2N1000	NPN-A		150	40		100S	35T*							
2N1008	PNP-A		167	20	300	75J	1.00						2N1415	24
2N1008A	PNP		167	40	300	85J	90T						2N526	24
2N1008B	PNP		167	60	300	85J	90T						2N1925	24
2N1009	PNP-A		150	25	20	85A	40T						2N395	24
2N1010	NP		20	10	2	85	35T						2N1694	24
2N1012	NP		150	40		100S	50T							
2N1015	NP		150 @ 45°C	30	75A	150	10*	2A	20T	Ke	20 ma	30		
2N1015A	NP		150 @ 45°C	60	75A	150	10*	2A	20T	Ke	20 ma	60		
2N1015B	NP		150 @ 45°C	100	7.5A	150	10*	2A	20T	Ke	20 ma	100		
2N1015C	NP		150 @ 45°C	150	7.5A	150	10*	2A	20T	Ke	20 ma	150		
2N1015D	NP		150 @ 45°C	200	7.5A	150	10*	2A	20T	Ke	20 ma	200		
2N1015E	NP		150 @ 45°C	250	7.5A	150	10*	2A	20T	Ke	20 ma	250		
2N1015F	NP		150 @ 45°C	300	7.5A	150	10*	2A	20T	Ke	20 ma	300		
2N1016	NP		150 @ 45°C	30	7.5A	150	10*	5A	20T	Ke	20 ma	30		
2N1016A	NP		150 @ 45°C	60	7.5A	150	10*	5A	20T	Ke	20 ma	60		
2N1016B	NP		150 @ 45°C	100	7.5A	150	10*	5A	20T	Ke	20 ma	100		
2N1016C	NP		150 @ 45°C	150	7.5A	150	10*	5A	20T	Ke	20 ma	150		
2N1016D	NP		150 @ 45°C	200	7.5A	150	10*	5A	20T	Ke	20 ma	200		