

| JEDEC No. | Type | Use | MAXIMUM RATINGS | | | | ELECTRICAL PARAMETERS | | | | | Closest GE | Dwg. No. | |
|-----------|---------|-----|--------------------------|-------------------------------------|-------------------|-------------------|---|--------------------------|------------------------|---|-------|------------|----------|----|
| | | | P _c mw @ 25°C | BV _{ce} BV _{CB} * | I _c ma | T _j °C | MIN. h _{fe} -h _{FE} * @ I _c ma | MIN. f _{hfb} mc | MIN. G _e db | MAX. I _{co} (μa) @ V _{CB} | | | | |
| 2N911 | NPN-PL | | 500 | 100 | | 200J | 50T | | | | | | | |
| 2N912 | NPN-PL | | 500 | 100 | | 200J | 30T | | | | | | | |
| 2N914 | NPN-PEP | Sw | 360 | 40 | | 200J | 30T | | | | | | 2N914 | 16 |
| 2N915 | NPN-PL | AF | 360 | 70 | | 200J | 40T | | | | | | 2N915 | 16 |
| 2N916 | NPN-PL | AF | 360 | 45 | | 200J | 50T | | | | | | 2N916 | 16 |
| 2N929 | NPN-PL | | 300 | 45 | | 175J | 40 | | | | | | 2N915 | 16 |
| 2N930 | NPN-PL | | 300 | 45 | | 175J | 100 | | | | | | 2N915 | 16 |
| 2N956 | NPN-PL | | 500 | 75 | | 200J | 100T | | | | | | 2N956 | 16 |
| 2N960 | PNP | Sw | 150 | 15 | | 100 | 20T | | | | | | | |
| 2N961 | PNP-EM | Sw | 150 | 12 | | 100 | 20T | | | | | | | |
| 2N962 | PNP-EM | Sw | 150 | 12 | | 100 | 20T | | | | | | | |
| 2N964 | PNP-EM | Sw | 150 | 15 | | 100 | 40T* | | | | | | | |
| 2N965 | PNP-EM | Sw | 150 | 12 | | 100 | 40T* | | | | | | | |
| 2N966 | PNP-EM | Sw | 150 | 12 | | 100 | 40T* | | | | | | | |
| 2N968 | PNP | | 150 | 15 | | 100J | 20T* | | | | | | | |
| 2N969 | PNP | | 150 | 12 | | 100 | 20T* | | | | | | | |
| 2N970 | PNP | | 150 | 12 | | 100 | 20T* | | | | | | | |
| 2N971 | PNP | | 150 | 7.0 | | 100 | 20T* | | | | | | | |
| 2N972 | PNP | | 150 | 15 | | 100 | 40T* | | | | | | | |
| 2N973 | PNP | | 150 | 12 | | 100 | 40T* | | | | | | | |
| 2N974 | PNP | | 150 | 12 | | 100 | 40T* | | | | | | | |
| 2N975 | PNP | | 150 | 7.0 | | 100 | 40T* | | | | | | | |
| 2N994 | PNP | Sw | 200 | 15 | | 150S | 75* | | | | | | | |
| 2N1000 | NPN-A | | 150 | 40 | | 100S | 35T* | | | | | | | |
| 2N1008 | PNP-A | | 167 | 20 | 300 | 75J | 1.00 | | | | | | 2N1415 | 24 |
| 2N1008A | PNP | | 167 | 40 | 300 | 85J | 90T | | | | | | 2N526 | 24 |
| 2N1008B | PNP | | 167 | 60 | 300 | 85J | 90T | | | | | | 2N1925 | 24 |
| 2N1009 | PNP-A | | 150 | 25 | 20 | 85A | 40T | | | | | | 2N395 | 24 |
| 2N1010 | NP | | 20 | 10 | 2 | 85 | 35T | | | | | | 2N1694 | 24 |
| 2N1012 | NPN-A | | 150 | 40 | | 100S | 50T | | | | | | | |
| 2N1015 | NPN | | 150 @ 45°C | 30 | 75A | 150 | 10* | 2A | 20T | Ke | 20 ma | 30 | | |
| 2N1015A | NPN | | 150 @ 45°C | 60 | 75A | 150 | 10* | 2A | 20T | Ke | 20 ma | 60 | | |
| 2N1015B | NPN | | 150 @ 45°C | 100 | 7.5A | 150 | 10* | 2A | 20T | Ke | 20 ma | 100 | | |
| 2N1015C | NPN | | 150 @ 45°C | 150 | 7.5A | 150 | 10* | 2A | 20T | Ke | 20 ma | 150 | | |
| 2N1015D | NPN | | 150 @ 45°C | 200 | 7.5A | 150 | 10* | 2A | 20T | Ke | 20 ma | 200 | | |
| 2N1015E | NPN | | 150 @ 45°C | 250 | 7.5A | 150 | 10* | 2A | 20T | Ke | 20 ma | 250 | | |
| 2N1015F | NPN | | 150 @ 45°C | 300 | 7.5A | 150 | 10* | 2A | 20T | Ke | 20 ma | 300 | | |
| 2N1016 | NPN | | 150 @ 45°C | 30 | 7.5A | 150 | 10* | 5A | 20T | Ke | 20 ma | 30 | | |
| 2N1016A | NPN | | 150 @ 45°C | 60 | 7.5A | 150 | 10* | 5A | 20T | Ke | 20 ma | 60 | | |
| 2N1016B | NPN | | 150 @ 45°C | 100 | 7.5A | 150 | 10* | 5A | 20T | Ke | 20 ma | 100 | | |
| 2N1016C | NPN | | 150 @ 45°C | 150 | 7.5A | 150 | 10* | 5A | 20T | Ke | 20 ma | 150 | | |
| 2N1016D | NPN | | 150 @ 45°C | 200 | 7.5A | 150 | 10* | 5A | 20T | Ke | 20 ma | 200 | | |