PRODUCTS
Rocker switches
Pushbutton switches
Toggle switches
Slide switches
Rotary switches
Foot switches
Tact and key switches
Snap-action switches
Micro-signal switches
ECO switches
Sensors
Push'n'Drive
Systems and modules
Accessories
General information
Catalog request / download

SERIES 1830 - SINGLE AND DOUBLE-POLE ROCKER SWITCHES - TO 20 (4) A 250 V AC

◂ Show previous product
Show next product ▸

1834.3312 | Drawing | Accessories

Similar to original product

→ Print data sheet

Product number	1834.3312
Actuator color / printing	
Switching function	Changeover switch (DPDT)
Number of poles	2-pole
connections	Quick-connect terminal, 6.3
Mechanical life endurance	10E4
Rating IEC	16 (4) A 250 V AC 1E4
Rating North America	16 A 125 V AC 1/4 HP 16 A 250 V AC 1/2 HP
Contact resistance (new condition)	< 100 (1 A 12 V DC) mOhm
Insulation resistance (new condition)	> 100 (500 V DC) MOhm
Proof tracking	250 PTI
Protection type	Connection IP40
Ambient temperature	-20 °C ... +105 °C
Ambient temperature	-20 °C ... +55 °C
Flammability	UL 94 V-2
Glow wire test temperature	850 °C
Actuators and additional actuators	PA, black
Housing description	PA, black
Connection surface	external connection silver plated
Contact material	Ag
Contact distance	≥ 3 mm
Plug force of the terminals	≤ 80 N
Approval marks	CSA / UL / ENEC 05
Suitable for appliances of protection class	II

 | Copyright 2014 Marquardt

Datasheet.Directory