

[PRODUCTS](#)

Rocker switches

[Pushbutton switches](#)[Toggle switches](#)[Slide switches](#)[Rotary switches](#)[Foot switches](#)[Tact and key switches](#)[Snap-action switches](#)[Micro-signal switches](#)[ECO switches](#)[Sensors](#)[Push'n'Drive](#)[Systems and modules](#)[Accessories](#)[General information](#)[Catalog request / download](#)
[PRODUCTS](#) ▶ [ROCKER SWITCHES](#)

SERIES 1830 - SINGLE AND DOUBLE-POLE ROCKER SWITCHES - TO 20 (4) A 250 V AC

[◀ Show previous product](#)
[Show next product ▶](#)

1834.3312

[Drawing](#)
[Accessories](#)


Similar to original product

[→ Print data sheet](#)

| Product number | 1834.3312 |
|---|---|
| Actuator color / printing |  |
| Switching function | Changeover switch (DPDT) |
| Number of poles | 2-pole |
| connections | Quick-connect terminal, 6.3 |
| Mechanical life endurance | 10E4 |
| Rating IEC | 16 (4) A 250 V AC 1E4 |
| Rating North America | 16 A 125 V AC 1/4 HP 16 A 250 V AC 1/2 HP |
| Contact resistance (new condition) | < 100 (1 A 12 V DC) mOhm |
| Insulation resistance (new condition) | > 100 (500 V DC) MOhm |
| Proof tracking | 250 PTI |
| Protection type | Connection IP40 |
| Ambient temperature | -20 °C ... +105 °C |
| Ambient temperature | -20 °C ... +55 °C |
| Flammability | UL 94 V-2 |
| Glow wire test temperature | 850 °C |
| Actuators and additional actuators | FA, black |
| Housing description | FA, black |
| Connection surface | external connection silver plated |
| Contact material | Ag |
| Contact distance | ≥ 3 mm |
| Plug force of the terminals | ≤ 80 N |
| Approval marks | CSA / UL / ENEC 05 |
| Suitable for appliances of protection class | II |

Datasheet.Directory