



## 1N5400G THRU 1N5408G

### GLASS PASSIVATED JUNCTION RECTIFIER

TECHNICAL  
SPECIFICATION


**VOLTAGE: 50 TO 1000V CURRENT: 3.0A**

#### FEATURES

- Molded case feature for auto insertion
- Glass passivated chip
- High current capability
- Low leakage current
- High surge capability
- High temperature soldering guaranteed:  
250°C/10sec/0.375" (9.5mm) lead length  
at 5 lbs tension

#### MECHANICAL DATA

- Terminal: Plated axial leads solderable per  
MIL-STD 202E, method 208C
- Case: Molded with UL-94 Class V-O  
recognized flame retardant epoxy
- Polarity: Color band denotes cathode
- Mounting position: Any



#### MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

(Single-phase, half-wave, 60Hz, resistive or inductive load rating at 25°C, unless otherwise stated, for capacitive load, derate current by 20%)

RATINGS	SYMBOL	1N54 00G	1N54 01G	1N54 02G	1N54 04G	1N54 06G	1N54 07G	1N54 08G	UNITS
Maximum Repetitive Peak Reverse Voltage	$V_{RRM}$	50	100	200	400	600	800	1000	V
Maximum RMS Voltage	$V_{RMS}$	35	70	140	280	420	560	700	V
Maximum DC Blocking Voltage	$V_{DC}$	50	100	200	400	600	800	1000	V
Maximum Average Forward Rectified Current (9.5mm lead length, at $T_L=105^\circ\text{C}$ )	$I_{F(AV)}$	3.0							A
Peak Forward Surge Current (8.3ms single half sine-wave superimposed on rated load)	$I_{FSM}$	200							A
Maximum Instantaneous Forward Voltage (at rated forward current)	$V_F$	1.0							V
Maximum DC Reverse Current $T_a=25^\circ\text{C}$ (at rated DC blocking voltage) $T_a=100^\circ\text{C}$	$I_R$	5.0 300							$\mu\text{A}$ $\mu\text{A}$
Typical Junction Capacitance (Note 1)	$C_J$	40							pF
Typical Thermal Resistance (Note 2)	$R_\theta(ja)$	30							$^\circ\text{C}/\text{W}$
Storage and Operation Junction Temperature	$T_{STG}, T_J$	-65 to +150							$^\circ\text{C}$

Note:

1. Measured at 1.0 MHz and applied voltage of 4.0V<sub>dc</sub>
2. Thermal resistance from junction to ambient at 0.375" (9.5mm) lead length, P.C. board mounted